


First TPB coating test and measurements

Silvestro di Luise 03/07/2017 Light Det. Sys. Meeting

- Restore evaporation system and check functionality:
 - Vacuum tightness, vacuum pumps
 - Cristal "evaporation" sensor
 - Heater/temperature sensors
- Evaporation on Mylar foils on PMT mockup








Cristal sensor: measure deposition rate of TPB. Used to checked that all TPB is evaporated

Vacuum measurement sensor. Two pumps, 1 turbo pump.







Before After

- Measure coating uniformity along the PMT surface
- Use glass cylinders samples mounted on 3D printed mockup





Longer vacuum pumping needed first likely due to plastic outgassing






Before After

TPB density along the PMT surface

TPB evaporated: 0.8 g



By weighting samples before/after the coating




Similar values obtained with Mylar foils (placed in the center of the PMT)

TPB density along the PMT surface

TPB evaporated: 0.8 g



By weighting samples before/after the coating




Similar values obtained with Mylar foils (placed in the center of the PMT)

TPB density along the PMT surface

TPB evaporated: 1.2 g



Only on a few samples



Summary

- Measurements performed last week with Maura Spanu (INFN) and Will Vollemberg (CERN).
- System operation is stable.
- Performed measurements of coating uniformity on glass.
- Mass coating. Evaporator is still in the old lab. I asked if possible to move it after we have done with the WA105 task. It should be possible. TBD.