
### **BSI Scope Final Design Changes**

Syd De Vries Arup Final Design Kick-Off Meeting November 7, 2017

#### <u>Surface Architectural - Ross Dry Renovations</u>


 Previously identified as a "Scope Option" with Control room kept in Scope

 Current scope does not include any renovations or Control Room construction except that which is required for fiber in the




#### **Underground Communications**

- Preliminary Design Scope for Leaky Feeder System Scope Option
- Final Design Scope To remain as a Scope Option




#### **Surface Electrical**

- Preliminary Design Scope for Surface Electrical included provision for design of Ross Surface Substation upgrades to be performed in Final Design
- Design for Ross Substation Upgrades has been completed in Pre-Excavation Final Design. Scope for Final Design requires inclusion of Costs for Transformer Installation in FD Cost estimate




#### **Surface Mechanical**

Current Preliminary
 Design utilizes
 Cooling Towers for
 100% Heat Rejection




#### Surface Mechanical

- Incorporate the plan from the Advanced Preliminary Design task for utilization of waste heat from the Cryogen compressors to heat the Intake Air for the Ross Shaft
- Cooling Towers are to remain to provide cooling during warm periods where Shaft Intake air does not require heating



#### Surface Civil - Cryogen Building


 Preliminary Design for the Cryogen Building considered only 1 Liquid Argon Storage Dewar and 1 Vaporizer



#### Surface Civil - Cryogen Building

 Final Design for the Cryogen must incorporate an additional 3 Liquid Argon storage dewars into the design

Also need 3 additional Liquid Argon Vaporizers




## Ross Shaft Headframe Strengthening Design – Foundations

- Current design based on visual assessment
- Design update required that incorporates more extensive in situ testing. This testing will be performed as part of EXC which will inform the design update to be completed as part of BSI



#### **Surface Structural – Ross Shaft Headframce**

 The current Preliminary Design does not provide for a Pipe Support structure to transition the Gas Piping from horizontal to vertical at the Shaft Collar. The Final Design will require this



#### **Underground Mechanical**


- Preliminary Design requirement for minimum Cavern Temperature – 40° F
- Final Design Change minimum 67° F

Table 6.13: Indoor Design Conditions by Space Type. [6] [21]

	DBT Minimum/ Maximum	RH Minimum/ Maximum	DPT Maximum	Minimum Ventilation Rate	Occupancy Assembly / Operation
Space Type	[°F]([°C])	[%]	[°F]([°C])	[-]	[#]
.01 ACCESS DRIFTS- 4850 LEVEL	40.0 / 104.0 (4.4 / 40.0)	Not Controlled	Not Controlled	Based on face velocity of 4m/s	0/0
.02 OTHER EXCAVATIONS	40.0 / 104.0 (4.4 / 40.0)	Not Controlled	Not Controlled	-	0/0
.03 CRYOSTAT/UTILI TY CAVERNS	67.0/85.0 67.0/85.0	15 / 85	48.0 (8.9)	Greater of 1 Air Change Per Hour or Oxygen Deficiency Hazard Limit	50 / 4

#### <u>Underground Electrical - Detector Electronics</u>

- Preliminary Design requirement for Detector Electronics 225
   KVA Transformers
- Final Design Change 500 KVA Transformers



#### **Underground Electrical - Detector Electronics**


- Preliminary Design requirement assumption for heat generated from Detector Electronics – 3 KW per Rack
- Final Design Change TBD

		Quantity		Electrical	Mechanical	Total	Total Waterside
Equipment	Quantity	Duty	Power	Heat Gain	l	Gain	Heat Gain
[-]	[#]	[#]	[W]	[W]	[W]	[W]	[W]
RP-48AS	1.00	1.00	0.00	0.00		0.00	0.00
10kT Cryostat	1.00	1.00			-32,100,00	-32,100,00	0.00
Detector Electronics Racks	77.00	77.00			3,0,100	2317.0.00	0.00

**TBD TBD** 

#### **Underground Electrical**


 Design for Underground Substation to be updated as per Advanced Preliminary Design Concept



**Current 100% Preliminary Design** 


#### **Underground Electrical**

- Design for Underground Substation to be updated as per Advanced Preliminary Design Concept
- Will also serve as Maintenance Shop during Excavation



#### **Underground Architectural/Electrical/Mechanical**


 Separate Maintenance Shop no longer required. Therefore, no additional BSI required for Maintenance Shop




11.07.17

#### **BSI Scope Changes – Underground Structural**

Add Vertical Unistruts on north wall of chamber to support Detector Pipe and




#### **BSI Scope Changes – Underground Structural**



11.07.17

# Underground Mechanical – Cryostat Ventilation

 A condensation analysis has been performed which has determined that the current Preliminary design for Cryostat ventilation does not provide for adequate circulation to prevent condensation from occurring



# Underground Mechanical – Cryostat Ventilation


Current Preliminary Design





**Exhaust Air** 

11.07.17




#### <u>Underground</u> <u>Mechanical –</u> <u>Cryostat</u> Ventilation

- Required
   Final Design
   Arrangement
- Required for all 4 Cryostat Chambers




**Exhaust Air** 

11.07.17



#### **Underground Communications**


 The Current Preliminary Design calls for a total of 16 racks in the CUC Communication room



#### **Underground Communications**

The Final Design requires a total of 52 racks in the CUC


Communication room



#### **Underground Plumbing**

 Modifications to the Shaft Set Steel design have been completed for sets 291 – 308. All Plumbing drawings need to be updated to incorporate the final design

Pre Excavation design for Piping in Shaft Services compartment at 305




PLAN VIEW SET 305

#### **Underground Plumbing**

Modifications to the Shaft Set Steel design have been completed for sets 291 – 308. All Plumbing drawings need to be updated to incorporate the final design

Updated Shaft Set steel design for Pipe Services compartment at set 305



#### **Underground Plumbing**

 Incorporate all outstanding comments from 100% Preliminary Design not completed

<u>Drawings</u>				
			We need to show the 3" Shaft Drain line	
SD033		PER-B-P-710	coming out of the shaft here	unresolved
			We need to show the 3" Shaft Drain line	
SD034		PER-B-P-717	coming out of the shaft here	unresolved
SD035		PER-B-P-720	Why does pipe ND move to the north slightly?	unresolved
			For this layout, PS-3 has been removed and	
SD039		PER-B-P-724	the pipe clamps are anchored to B09	unresolved
			We need to show the 3" Shaft Drain line	
SD040		PER-B-P-725	coming out of the shaft here	unresolved
			Consistent with my comment SD026, the FW	
			and IW pipes should go to the west rather	
SD043		PER-B-P-732	than the east	unresolved
			Detail 1 - DW 10 01 Pipe Clamps - there are	
SD008	BSI	PER-B-P-801	no detailed dimensions shown in this design.	unresolved
			Detail 1 - DW 10 01 Pipe Clamps - not sure	
			about the clamp thickness but it sure looks	
SD009	BSI	PER-B-P-801	thicker than necessary for a 10" pipe	unresolved
			Between sets 207 and 208, the 8" ND line	
			moves slightly to the west. This should be	
			shown in the Revit view with an elbow along	
SD013	BSI	PER-B-P-720	this pipe somewhere between the 2 sets	unresolved
			All the pipe clamp drawings say that the	
			fasteners are FRA supplied. This comment	
			should be removed. We want the cost of the	
SD022	BSI	PER-B-P-800 series	fasteners included in the estimate	unresolved

#### **Potential Changes**

Po	tential Change Description	Status	
1.	Electrical/Data Support for Infrared Cameras to Monitor Cryostat Performance	Waiting for Clarification from Cryostat Group	
2.	Emergency Shut off Switches for Power Distribution. Could be for CF as well as EXP	Waiting for further clarification	
3.	Connections for Lighting and Fire Protection below the Mezzanine Level	Requirement Definition Required	
4.	Piping and Electrical run through a trench in the Septum	Requires Trade Study	
5.	Integration of Access Control System	Under Investigation	
6.	Industrial Water, Compressed Air and Emergency Communications at the Chamber bottom	Requirement Definition Required	
7.	Addition of temporary grounding network to the bottom of each Detector Pit	Requirement Definition Required	

#### **Potential Changes Cont'd**

Potential Change Description	Status		
8. Infirmary and Recreation Room in CUC	Special Committee set up to determine if required		
9. Machine Shop for Cryostat Construction	Further Clarification Required		

### Questions?