
A photograph of a large, classical-style building with white columns and a portico, surrounded by many tall palm trees. A rainbow is visible in the sky above the building. The scene is set outdoors on a clear day.

# Calibration Insertion System of DarkSide-50 experiment


Jelena Maricic

University of Hawaii

# Introduction





- Between 2014 – 2017 we have designed, fabricated, commissioned and deployed calibration system for the DarkSide experiment called CALibration Insertion System (CALIS).
- During this period, several calibration campaigns have been executed: AmBe, AmC,  $^{137}\text{Cs}$ ,  $^{133}\text{Ba}$ ,  $^{57}\text{Co}$ ,  $^{22}\text{Na}$
- Engineering design came from Cary Kendziora (Fermilab engineer), while fabrication, assembly and testing were carried out at Hawaii and FNAL, prior to commissioning at GranSasso in the DarkSide veto.
- Material and fabrication cost were very modest \$20k (engineering cost not included). Also utilized university paid machinist and CNC machine capabilities – only material cost incurred.




# DarkSide-50 experiment

- DarkSide-50 experiment is dual phase argon TPC located in Gran Sasso Italy.
- Is the direct dark matter search experiment.
- Looks for nuclear recoils as signature of WIMP recoil in the detector.
- Background free high mass WIMP search.
- Currently holds the best low energy WIMP limit.







# CALIS in DarkSide-50



- Vacuum tight enclosure located on the top
- Gate valve at the top to seal the detector while not in use
- Source is mounted at end of the arm
- Arm can be rotated to bring source to different locations during single deployment.

Arm  
Can rotate  
To bring  
Sources to TPC  
Or elsewhere

# CALIS design




- Two cables mounted on two spools are connected at the bottom with a chain that goes over the disk.
- The source is mounted on the tip of the arm
- Arm is rigidly mounted on the center of the disc.
- After the source is mounted, gate valve is opened, and source is deployed to desired z position, while two cables unwind in parallel with stepper motor.

## DarkSide-50 radon-free clean room


cryo  
tower

CALIS

electronics rack





## System as built



Efficient purging by multiple  
cycles of nitrogen and  
Filling and vacuum pumping.


Important to eliminate residue  
scintillator after  
deployment, as well oxygen and  
humidity prior to deployment

# Detail of the Arm and Rotation




- Once in z position, one of the cables is shortened for  $\frac{1}{4}$  cycle of the disc, rotating the disc, and placing the arm in the horizontal position, close to TPC.



Stepper Motor




# Spools and articulation




- In order to rotate the arm, small handle on the right spool is turned, turning the right spool and winding up the right-hand cable.
- As a result chain around the disc moves, rotating the disc and arm with source.









# Rotation in vertical plane toward TPC






# Phi rotation in the horizontal plane




- Performed manually.
- Allows full 360°
- System rotates easily and does not leak.
- Helium leak test checked.




# Safety features

- Motor features absolute encoder, so position is NEVER lost.
- Possibility to retract the cable manually in case of cable failure.
- Multiple push buttons and stranded cables used to secure the source to the disc of the calibration system
- Hardware limit switches installed:
  - Cuts power to the motor, if arm rotation is attempted in the pipe, prior to reaching the veto.
  - Cuts power to the motor, if arm is not rotated back to vertical position, prior to retraction to the top.
  - Cut power to the motor, if the number of steps sends the system higher than home position.

# Summary - calibration insertion system



- CALIS allows good range of deployment positions in xyz.
- Built with very modest funds.
- Inside clean room
- This system can be modified for DUNE FD as needed.
- The most important at this point are INTERFACES of calibration with other systems: flange on the veto... & available overhead space



AmBe before and after neutron selection cuts