

Update on H₂ Recombination

T. Sekiguchi




2019. 12. 6



- **New resin**

- Resins produced by LANXESS and its performance proved by EBARA
- I contacted the person in charge of the new resin and he was very interested in the application of this resin
- As a trial, this resin was put into one IE bottle for a test
 - 4L of the old resins were replaced with new ones
- To be tested during next beam time



Remove existing resins




Put new resins



Completed IE bottle




New resin (~4L)
is overlaid



50 L in total

Ion Exchanger Effect on H₂ Concentration



Run period	Run6	Run7	Run8	Run9-1	Run9-2	Run9-3	Run10
Configuration	Single (old)	Single (new)	Single (old)	Dual (new)	Single (new)	Single (new)	Single (new)
Beam power (kW)	330	390	470	450	475	485	420~496
H ₂ concentration (%)	0.4	2.5	1.5	4.0	1.0	2.4	1.4
Production rate (% / 10 ¹⁹ POT)	0.173	0.683	0.215	0.832	0.299	0.137	< 0.303


- H₂ production rate rapidly increased after Ion exchanger replacement
- Production rate with new Ion Exchanger (IE) is almost comparable to that with usual new IE



Water Conductivity Trend in Past Runs



- **Water conductivity**

- A strange behavior during dual IE operation
- Low conductivity during single IE operation, **but still increased in a week**
- Conductivity got increased around middle of April
 - This indicates lifetime of IE \Rightarrow **$\sim 6.0 \times 10^{20}$ POT (or 2~3 months)**





- Both H₂ production rate and conductivity got decreased as beam power increased
- Conductivity is quite stable
- Long-term performance (such as lifetime) should be checked
- Also good to measure H₂O₂ concentration in the cooling water





- FY2019
 - Check the long-term performance of the new IE
 - Preparation for modification of O₂ degasifier system
- FY2020
 - Complete the O₂ degasifier system and operate it during next beam operation (in Fall 2020)