



Locking Cavity 2A

Matthew Taubman

ADMX Collaboration Meeting, November 2020

Noah Oblath, Christian Boutan,

Daniel Cain, Ben LaRoque



PNNL is operated by Battelle for the U.S. Department of Energy

Unclassified and Not Sensitive, 2020-11-16






Outline

- ADMX Cavity 2A Locking Scheme
- Operational Flow Charts
 - Locking / Tuning a single cavity
 - Locking to Target
 - Locking to Average
- Requirements
 - Precision
 - Speed
 - Heating
- Performance
 - Precision
 - Speed
 - Heating (Steps)
- Pathway forward
 - Move to Cool Prototype Array
 - Move to Final Cavity Array
 - Support


ADMX 2A Locking Scheme

- TM010 Cavity Resonance
- Moved by adjusting Fine Turning Rod
- Detuning detected by VNA
- Locking algorithm drives PZT Motor Controllers
- => Detuning driven to (near) zero




Flow Charts – Locking / Tuning a Cavity

Tune Single Cavity




Flow Charts – Locking to Target Frequency





Flow Charts – Locking to Average






Requirements

- Precision
 - All four cavities should be locked within 10% of their line width (FWHM)
- Speed / Time
 - All four cavities should be locked within 10 seconds for each frequency step
- Power Dissipation / Heating
 - The locking process should produce less than 10 mW on average during the process

Performance

- Testing
 - PNNL working directly with Fermilab to lock Prototype Cavity Array
 - All tests to date have been warm
- Locking Scripts
 - Debugged and Automated
 - Dripline and Virtual Environments Operational
- Cavities
 - Most tests with Cavities A, B, D.
 - C recently came online – need to adjust flexure
 - Nominal line width is 900 kHz (warm)
 - Nominal Q ~ 6000 (warm)





Run 2A Cavity System





Precision $\pm 1\%$ to $\pm 1.5\%$

- Routinely achieving $\pm 1\%$ to $\pm 1.5\%$
- Clumping due to VNA digitization/resolution









Pacific Northwest
NATIONAL LABORATORY

Speed Median < 1.5 sec

- Nearly always under 2.5 sec / Cavity
- Median is below 1.5 sec / Cavity
- (Cavity C is currently slower)







Unclassified and Not Sensitive, 2020-11-16



Heating (Steps)

- Varies with Cavity
- Median between 130 and 295
- Haven't extrapolated to heating yet
 - we expect things to change when we cool the cavities



Pathway Forward

- Move to Cool the Prototype Array
 - Certain things will change, including Q and PZT Motor transfer functions
 - ✓ Hopefully in a concomitant way...
 - ✓ ... Higher Q, and smaller frequency shift per step
 - Locking System Adjustments
 - ✓ Should be relatively minor
 - ✓ System should remain automated for testing
- Move to Final Cavity Array
 - Full Characterization Warm
 - Characterization Cold
 - Locking Testing Cold
 - Commissioning
- Support





Summary

- Implemented Four Cavity Locking on Prototype Array at Fermilab
- Meeting Speed and Precision Requirements
- Heating not yet ascertained but expected to easily meeting requirements
- Need to discuss next moves
 - Limited funding
 - Delays
 - Do we test prototype cavities cold?
 - ... Or wait for final cavity array?





Thank you

Unclassified and Not Sensitive, 2020-11-16

