



Dipole Survey and Alignment of NSLS-II

M. Ke, S. Seiler, F. Karl, M. Ilardo, C. Yu, R. Hubbard, D. Davis,
S. Pop, L. Borak, D. Gordon, E. Ulrich, R. Craig, BNL, US

Introduction

The survey group of Brookhaven National Laboratory (BNL) undertakes the entire alignment task across the lab which includes NSLS, NSLS-II, AGS, RHIC and etc. NSLS-II is an on-going project which will be a new state-of-the-art, medium-energy electron storage ring (3 GeV, 30 DBA) designed to deliver world-leading intensity and brightness with a 0.6 nmrad minimum horizontal emittance when it's fully built out. It will provide 1 nm spatial resolution and 0.1 MeV energy resolution to facilitate the study of nanostructures. Its circumference is 792 meter with the potential of at least 58 beamlines. The construction of the NSLS-II's ring building began in March 2009 and it's scheduled to be in full operation in June 2015.

There are 60 dipole girders and 90 multipole girders totally. NSLS-II project requires ± 100 micron alignment accuracy between girders. The work associated with dipoles can be categorized as pre-survey portion and alignment portion. The pre-survey of dipoles includes mechanical frame establishment, manufacturing dimension and vacuum clearance verification. The alignment portion includes the positioning of dipole relative to magnetic measurement system and tunnel positioning relative to control network.




Dipole Parameters			
Dipole Type	Type	A	B
Aperture, minimum	mm	35	90
Operating DC Field	T	0.4	0.4
Magnetic Length	mm	2620	2620
Radius of beam axis	m	25.02	25.02
Tolerance on yoke radius (\pm)	mm	50	50
Yoke Length, nominal	mm	2584	2528
Lamination Thickness, nominal	mm	1	1

The Characteristic of Dipole

Dipole are laminated but have machined pole surface which means the pole surface can represent the geometry information and be used as survey reference.


Compared with multipoles, the magnet dimension is bigger. Laser tracker, not articulated arm, with scanning capability is used to perform the survey.




Dipole Pre-survey

When a dipole is ready to be inspected, there are 3~4 laser tracker setups in order to capture all the information needed. The measurement elements include:


- Common targets are measured during each setup to orient instruments. Unified Spatial Metrology Network (USMN) of Spatial Analyzer (SA) is used to get the optimal coordinates.
- Pole surfaces points are measured to define the horizontal plane and can be used to compute the aperture of the dipole.
- Points are measured on the upstream and downstream end of the top and bottom poles to control the beam longitudinal position.
- Inboard and outboard circle points can determine the bending radius. The bisected circle defines the beam orbit.
- The magnet frame can be established and the information is ready for further alignment.
- Some measurements are dedicated for Interface Control Drawing (ICD) check purpose, such as the end and bottom of coil position, mounting holes in the base etc. Inspection report will be generated for each dipole. Discrepancy report will be submitted if the dimension is out of tolerance.



NSLS-II Storage Ring									
1	2	3	4	5	6	7	8	9	10
11	12	13	14	15	16	17	18	19	20
21	22	23	24	25	26	27	28	29	30
31	32	33	34	35	36	37	38	39	40
41	42	43	44	45	46	47	48	49	50
51	52	53	54	55	56	57	58	59	60
61	62	63	64	65	66	67	68	69	70
71	72	73	74	75	76	77	78	79	80
81	82	83	84	85	86	87	88	89	90
91	92	93	94	95	96	97	98	99	100
101	102	103	104	105	106	107	108	109	110
111	112	113	114	115	116	117	118	119	120
121	122	123	124	125	126	127	128	129	130
131	132	133	134	135	136	137	138	139	140
141	142	143	144	145	146	147	148	149	150
151	152	153	154	155	156	157	158	159	160
161	162	163	164	165	166	167	168	169	170
171	172	173	174	175	176	177	178	179	180
181	182	183	184	185	186	187	188	189	190
191	192	193	194	195	196	197	198	199	200
201	202	203	204	205	206	207	208	209	210
211	212	213	214	215	216	217	218	219	220
221	222	223	224	225	226	227	228	229	230
231	232	233	234	235	236	237	238	239	240
241	242	243	244	245	246	247	248	249	250
251	252	253	254	255	256	257	258	259	260
261	262	263	264	265	266	267	268	269	270
271	272	273	274	275	276	277	278	279	280
281	282	283	284	285	286	287	288	289	290
291	292	293	294	295	296	297	298	299	300
301	302	303	304	305	306	307	308	309	310
311	312	313	314	315	316	317	318	319	320
321	322	323	324	325	326	327	328	329	330
331	332	333	334	335	336	337	338	339	340
341	342	343	344	345	346	347	348	349	350
351	352	353	354	355	356	357	358	359	360
361	362	363	364	365	366	367	368	369	370
371	372	373	374	375	376	377	378	379	380
381	382	383	384	385	386	387	388	389	390
391	392	393	394	395	396	397	398	399	400
401	402	403	404	405	406	407	408	409	410
411	412	413	414	415	416	417	418	419	420
421	422	423	424	425	426	427	428	429	430
431	432	433	434	435	436	437	438	439	440
441	442	443	444	445	446	447	448	449	450
451	452	453	454	455	456	457	458	459	460
461	462	463	464	465	466	467	468	469	470
471	472	473	474	475	476	477	478	479	480
481	482	483	484	485	486	487	488	489	490
491	492	493	494	495	496	497	498	499	500
501	502	503	504	505	506	507	508	509	510
511	512	513	514	515	516	517	518	519	520
521	522	523	524	525	526	527	528	529	530
531	532	533	534	535	536	537	538	539	540
541	542	543	544	545	546	547	548	549	550
551	552	553	554	555	556	557	558	559	560
561	562	563	564	565	566	567	568	569	570
571	572	573	574	575	576	577	578	579	580
581	582	583	584	585	586	587	588	589	590
591	592	593	594	595	596	597	598	599	600
601	602	603	604	605	606	607	608	609	610
611	612	613	614	615	616	617	618	619	620
621	622	623	624	625	626	627	628	629	630
631	632	633	634	635	636	637	638	639	640
641	642	643	644	645	646	647	648	649	650
651	652	653	654	655	656	657	658	659	660
661	662	663	664	665	666	667	668	669	670
671	672	673	674	675	676	677	678	679	680
681	682	683	684	685	686	687	688	689	690
691	692	693	694	695	696	697	698	699	700
701	702	703	704	705	706	707	708	709	710
711	712	713	714	715	716	717	718	719	720
721	722	723	724	725	726	727	728	729	730
731	732	733	734	735	736	737	738	739	740
741	742	743	744	745	746	747	748	749	750
751	752	753	754	755	756	757	758	759	760
761	762	763	764	765	766	767	768	769	770
771	772	773	774	775	776	777	778	779	780
781	782	783	784	785	786	787	788	789	790
791	792	793	794	795	796	797	798	799	800
801	802	803	804	805	806	807	808	809	810
811	812	813	814	815	816	817	818	819	820
821	822	823	824	825	826	827	828	829	830
831	832	833	834	835	836	837	838	839	840
841	842	843	844	845	846	847	848	849	850
851	852	853	854	855	856	857	858	859	860
861	862	863	864	865	866	867	868	869	870
871	872	873	874	875	876	877	878	879	880
881	882	883	884	885	886	887	888	889	890
891	892	893	894	895	896	897	898	899	900
901	902	903	904	905	906	907	908	909	910
911	912	913	914	915	916	917	918	919	920
921	922	923	924	925	926	927	928	929	930
931	932	933	934	935	936	937	938	939	940
941	942	943	944	945	946	947	948	949	950
951	952	953	954	955	956	957	958	959	960
961	962	963	964	965	966	967	968	969	970
971	972	973	974	975	976	977	978	979	980
981	982	983	984	985	986	987	988	989	990
991	992	993	994	995	996	997	998	999	1000



Dipole in SR



```
// SpatialAnalyzer SA 2012.07.09
// Points Relative to Coordinate Frame 'A': MIDDLE OF PROBES AT
// HOME-S-10-11"
// AXES = CARTESIAN: X, Y, Z [Millimeters]
US MEAS, 200.632991, 0.004002, 3806.423923
C MEAS, 166.964773, 0.001429, 2308.331910
DS MEAS, 200.692471, -0.005951, 1010.239900
US RNOH, 200.633003, 0.044741, 3806.424008
ORIGIN RNOH, 166.964775, 0.035352, 2308.332028
DS RNOH, 200.692469, 0.021688, 1010.239980
RADIUS POINT, 25185.964718, -1.551501, 2308.904342
DPL-3500-SN 0024 ORIGIN, 166.964775, 0.035352, 2308.332028
DPL-3500-SN 0024 X AXIS, -833.035121, 0.008778, 2308.330182
DPL-3500-SN 0024 Y AXIS, 167.028201, 1000.035350, 2308.332150
DPL-3500-SN 0024 Z AXIS, 166.967850, 0.036473, 1308.332028
HOME ORIGIN, 0.000000, 0.000000, 0.000000
HOME X AXIS, 1000.000000, 0.000000, -0.000000
HOME Y AXIS, 0.000000, 1000.000000, 0.000000
HOME Z AXIS, 0.000000, 0.000000, 1000.000000
```

Notes:
A "BEAMLINE" circle is built so that it is at the mechanical center of the magnet with the nominal radius (25019 mm). The US and DS planes are defined by the ends of the noses and the vertical midplane is the bisecton of these.
US RNOH, ORIGIN RNOH, and DS RNOH are points where the "BEAMLINE" circle passes through these vertical planes.
The new points US MEAS, C MEAS, and DS MEAS are the three points from which the "BEAMLINE" circle is made.
These have different elevation coordinates (Y) because the "BEAMLINE" circle is not only made with a fixed radius, but also is projected to the HORIZONTAL MIDPLANE based on the measured "bumps" of the poles.
RADIUS POINT is the center of the magnet's "BEAMLINE" circle.

Dipole Installation in Storage Ring

Dipole girder installation in storage ring (SR) will be a 2-step process.

- Dipole girder will be aligned relative to control network with about ± 200 micron precision. Similar with the alignment of multipole girders, two trackers will be employed at the same time to streamline the adjustment process. There has been about 1/5 of the dipole girders have been aligned this way by the end of August, 2012.
- Next year, when the settlement of tunnel stabilizes and the environmental control are fully in action, multipole girders will be gone through a very precise girder profile reproduction process as reported in this workshop. Along with that kind of activity, dipole girder will be re-aligned relative to the adjacent multipole girders and the girder alignment specification will be pursued and achieved.

Alignment Error Estimate

Dipole girder alignment error can be estimated based on the following error source:

- Pre-survey precision: $\sim \pm 50$ micron.
- Tunnel control network: $\sim \pm 70$ micron.
- Alignment residual: $\sim \pm 50$ micron.
- The final alignment precision is about ± 100 micron.

Instrument and Software

The major instruments used in NSLS-II project are laser trackers, articulated arms and total stations. In the early stage, mekometer and digital level were used to establish the primary and elevation control network, but they were phased out.

Star*net is used to analyze the control network data initially and double check the data obtained from SA occasionally. The major software in use is SA. We have 12 SA keys to ensure the seamless transfer of data among the group members. The uniform interface and versatile functionality of the software is very helpful to the project. Especially, the data analysis for dipole pre-survey can be automated with the help of the Measurement Plan (MP). It has been proven to be very effective. Although the writing and debugging MP need some time, the result can be provided in a timely manner after the raw data is obtained.

Acknowledgment

The authors would like to thank all the staff who got the work done.

Questions? Ask me ...

Ming Ke: mke@bnl.gov



12th International Workshop on Accelerator Alignment (IWAA 2012)

September 10-14, 2012 Fermilab, Batavia, Illinois, US