

# Calibration and Standardization of Large Surveys and Missions in Astronomy and Astrophysics



Contribution ID : 21

Type : **not specified**

## DECal: A Spectrophotometric Calibration System For DECam.

*Monday, April 16, 2012 4:20 PM (0:20)*

### Abstract content

DECal is a new spectrophotometric calibration system for the CTIO Blanco 4 meter telescope. It is currently being installed as part of the Dark Energy Survey. The system uses a tunable light source to measure the wavelength-dependent instrumental response function of the total telescope+instrument in the range  $300 < \lambda < 1100 \text{nm}$ . The calibration will be performed regularly to monitor changes in telescope throughput during the 5 year Dark Energy Survey project. DECal consists of a monochromator-based tunable light source that is projected on a Lambertian flat field screen using a broadband “line to spot” fiber bundle and an engineered diffuser. Several calibrated photodiodes positioned along the beam monitor the telescope throughput as a function of wavelength. DECal has a peak output power of 2 mW, equivalent to a flux of approximately 800 photons/s/pixel on DECam.

### Summary

**Primary author(s)** : Dr. MARSHALL, Jennifer L. (Texas A&M University)

**Co-author(s)** : RHEAULT, Jean-Philippe (Texas A&M University); Prof. DEPOY, D. L. (Texas A&M University); PROCHASKA, Travis (Texas A&M University); ALLEN, Richard (Texas A&M University); WISE, Jason (Texas A&M University); MARTIN, Emily (Texas A&M University)

**Presenter(s)** : Dr. MARSHALL, Jennifer L. (Texas A&M University)

**Session Classification** : Session 1D

**Track Classification** : Calibration of instruments/telescopes before and after deployment