

Beamline Simulation Effort for ν STORM

Ao Liu

Fermi National Accelerator Laboratory

Indiana University Joint PhD Program

September 22, 2012

Outline

- 1 This is a progress report on beam simulations of transportation of pions captured by a magnetic horn downstream into a muon storage ring. Including:
- 2 **MAD8 and OptiM Simulation**
 - MAD8 and OptiM are used and combined to match the optics and generate lattice input for G4Beamline
- 3 **G4Beamline Simulation**
 - Real-field plus Multi-particle tracking for transport line with reference particle tuning for the ring, and dynamic aperture calculations



Purpose of study

- 1 In LOI we have proposed a pion production efficiency together with collection efficiency of 0.1 pions per proton on target, with an efficiency of 0.8 for transport, 0.9 for injection. Namely 0.072 pions per POT will be delivered to the ring;
- 2 Now let's look at what we can obtain according to simulation


ν STORM Target

Table I. π^+ yield/POT with 60 GeV/c protons, into 2 mm radian acceptance.

material	momentum (GeV/c)	$\pm 15\%$	$\pm 10\%$	$\pm 5\%$	target length (cm)	density (g/cm ³)
Carbon	3	0.085	0.056	0.028	27.3	3.52
Carbon	5	0.099	0.067	0.033	32.2	3.52
Inconel	3	0.131	0.087	0.044	19.2	8.43
Inconel	5	0.136	0.091	0.045	27.0	8.43
Tantalum	3	0.164	0.109	0.054	15.3	16.6
Tantalum	5	0.161	0.107	0.053	21.3	16.6
Gold	3	0.177	0.118	0.059	18.0	19.32
Gold	5	0.171	0.112	0.056	21.0	19.32

- Able to achieve ~ 0.11 pions per POT in $\pm 10\%$ momentum bin;
- Medium/Heavy targets preferred;
- Courtesy of Sergei Striganov (MARS simulation)

Pion Phase-Space Distribution after Target



Total pions per POT = 0.137. Different color represents different intensity inside that pixel;

Pion distribution at 10 cm after target.
Vertical axis: Angle; horizontal axis: Position

Pions per POT in 2 mm-rad which is the acceptance of the ring we are now considering = 0.114 (~84%)



Pion Capture


- We have looked into two schemes to capture the π 's:
Lithium lens or Horn;
- A lithium lens configuration which could make capture work well according to simulation was beyond the state-of-the-art for an operating lens.
- Using a NuMI-like, 250 cm long horn seems to be a better choice→**0.116** pions are collected out of 0.137 pions / POT after target(85%). In the ring's 2 mm-rad acceptance, 0.084 out of 0.114 pions / POT (74%) are collected. (See picture in next slide)

Pion Capture(Cont'd)

Total yield of pions is 0.116 pions POT

Inside the 2 mm-rad acceptance ellipse: 0.084 pions POT are captured

60 GeV proton, $\sigma_x=\sigma_y=0.15$ mm
 $\pi^- - \delta p/p=0.1$, $\varepsilon=2$ mm rad, $\beta=552.5$ cm, $\alpha=0$



Pion distribution at downstream of the horn. Vertical axis: Angle; Horizontal axis: Position.




Summary of target and capturing:

We were able to achieve LOI proposed 0.1 pions per POT with a Tantalum or Gold target and a magnetic horn.

Stochastic Injection

- New injected beam separated with circulating beam by their different momenta.
- Want to store 0.1-0.2 muons / pion
- No need for a separate decay channel;
- No need for full-aperture fast kickers;
- Beam pulse as long as the Main Injector Circumference (3000 m) can be used.





Goals for transport line study

- Fit the beam transport in MAD8 to
 - Match C-S parameters and dispersion from downstream of the horn to decay ring straight section;
 - Lower beta functions and dispersion to decrease the beam size as much as possible;
 - Also needs to count in the cost of magnet configurations(Try to keep low gradient and keep physical sizes of quadrupoles as few as possible)
- Understand the transmission efficiency of the transport line in G4Beamline - Find the pion flux delivered to the ring;

Matching into a symmetric FODO ring

Beta functions in straight = 20 to 30 meters (which gives beam radius size ~ 0.25 m, and RMS divergence 0.0041 to 0.005. Recall that $1/\gamma \sim 0.03$); straight section length ~ 260 m. 60% injected pions decay in the straight.

Max β 's in the arc ~ 11 to 12 m; arc section length ~ 60 m. Straight to arc ratio ~ 3.833



Injection-Ring common section, after which $D_x=0$, $\alpha_x=\alpha_y=0$, $\beta_x=9.77$ m, $\beta_y=3.16$ m


Total length of 645 meters

Matching into my symmetric ring(Cont'd)

Maximum beta function around 10.3 meters

Total length of 19.2 m; time of flight 64 ns; in pion's frame 1.8 ns; fraction decayed $1 - \exp(-1.8/26) \sim 6.7\%$

Maximum Dispersion ~ 0.5 m. Approximate beam radius $\sim \sqrt{\beta \epsilon + D \frac{\Delta P}{P}} = 20$ cm




Script conversion from OptiM lattice to G4BL— opttog4bl.csh version 1.05i

```

[aoa-macbook-pro:~] aoa@liu:~/research/FNAL/matched$ aoa@liu:~/research/FNAL/matched$ ./opttog4bl.csh DaveRing.lattice
### Notice that the decay is disabled, the max circulation # for a ring is now set to 2.
### Instructions are given in the .g4bl, you may change the parameters above by yourself.
### Please make sure that your file doesn't have no-length physical elements like dipoles, quads, etc.
### Ao Liu's opttog4bl.csh; Version 1.04 ### frankliuao.com
Input your reference particle momentum:(IN MeV)
3800
Input your particle; see G4BL manual for supported ones. e.g. 'pi+' 'mu-' 'e+'...
mu+
Input your rigidity in T.m:
12.66
Input your default beam pipe RADIUS: (in mm)
300
Fringe field wanted? Type 1 for yes, 0 for no.
0
Do you want to calculate Dynamic Aperture? See readme for help; If not you need to specify the initial beam def. yourself. See
G4Beamline manual for beam types;
Please prepare your approximated phase space full-acceptance ranges for x and dx/dz to calculate;
Type 1 for yes, 0 for no
1
Input your half-width(mm) RANGE for x; e.g. 20 means approximately x range is in 0+-20mm
280
Input half-width RANGE for dx/dz; e.g. 0.02 means approx. x' range is 0+-0.02
0.02
Input momentum spread deltaP/P; e.g. 0.1 means refP +- 0.1*refP
0.1
How many turns do you want? (For a ring). Input 1 for a single turn or a line structure
1000
Do you want your dipole tuned? Will take some time; 1 for yes 0 for no
1
Running opttog4bl.csh
014 017 797 36.6453 0 -1.057
014 014 954.443 36.6453 0 -1.057
016 016 989.781 35.1382 0 0.896507
017 017 1013.86 43.8794 0 0.896507
018 018 1077.54 43.8794 0 0.896507
019 019 1108.65 231.106 0 0.896507
020 020 1158.65 50 0 -0.999364
021 021 1182.65 25 0 0.896507
022 022 1202.65 25 0 0.896507
023 023 1222.65 25 0 0.896507
024 024 1242.65 25 0 0.896507
025 025 1262.65 25 0 0.896507
026 026 1282.65 25 0 0.896507
027 027 1302.65 25 0 0.896507
028 028 1322.65 25 0 0.896507
029 029 1342.65 25 0 0.896507
030 030 1362.65 25 0 0.896507
031 031 1382.65 25 0 0.896507
032 032 1402.65 25 0 0.896507
033 033 1422.65 25 0 0.896507
034 034 1442.65 25 0 0.896507
035 035 1462.65 25 0 0.896507
036 036 1482.65 25 0 0.896507
037 037 1502.65 25 0 0.896507
038 038 1522.65 25 0 0.896507
039 039 1542.65 25 0 0.896507
040 040 1562.65 25 0 0.896507
041 041 1582.65 25 0 0.896507
042 042 1602.65 25 0 0.896507
043 043 1622.65 25 0 0.896507
044 044 1642.65 25 0 0.896507
045 045 1662.65 25 0 0.896507
046 046 1682.65 25 0 0.896507
047 047 1702.65 25 0 0.896507
048 048 1722.65 25 0 0.896507
049 049 1742.65 25 0 0.896507
050 050 1762.65 25 0 0.896507
051 051 1782.65 25 0 0.896507
052 052 1802.65 25 0 0.896507
053 053 1822.65 25 0 0.896507
054 054 1842.65 25 0 0.896507
055 055 1862.65 25 0 0.896507
056 056 1882.65 25 0 0.896507
057 057 1902.65 25 0 0.896507
058 058 1922.65 25 0 0.896507
059 059 1942.65 25 0 0.896507
060 060 1962.65 25 0 0.896507
061 061 1982.65 25 0 0.896507
062 062 2002.65 25 0 0.896507
063 063 2022.65 25 0 0.896507
064 064 2042.65 25 0 0.896507
065 065 2062.65 25 0 0.896507
066 066 2082.65 25 0 0.896507
067 067 2102.65 25 0 0.896507
068 068 2122.65 25 0 0.896507
069 069 2142.65 25 0 0.896507
070 070 2162.65 25 0 0.896507
071 071 2182.65 25 0 0.896507
072 072 2202.65 25 0 0.896507
073 073 2222.65 25 0 0.896507
074 074 2242.65 25 0 0.896507
075 075 2262.65 25 0 0.896507
076 076 2282.65 25 0 0.896507
077 077 2302.65 25 0 0.896507
078 078 2322.65 25 0 0.896507
079 079 2342.65 25 0 0.896507
080 080 2362.65 25 0 0.896507
081 081 2382.65 25 0 0.896507
082 082 2402.65 25 0 0.896507
083 083 2422.65 25 0 0.896507
084 084 2442.65 25 0 0.896507
085 085 2462.65 25 0 0.896507
086 086 2482.65 25 0 0.896507
087 087 2502.65 25 0 0.896507
088 088 2522.65 25 0 0.896507
089 089 2542.65 25 0 0.896507
090 090 2562.65 25 0 0.896507
091 091 2582.65 25 0 0.896507
092 092 2602.65 25 0 0.896507
093 093 2622.65 25 0 0.896507
094 094 2642.65 25 0 0.896507
095 095 2662.65 25 0 0.896507
096 096 2682.65 25 0 0.896507
097 097 2702.65 25 0 0.896507
098 098 2722.65 25 0 0.896507
099 099 2742.65 25 0 0.896507
100 100 2762.65 25 0 0.896507
101 101 2782.65 25 0 0.896507
102 102 2802.65 25 0 0.896507
103 103 2822.65 25 0 0.896507
104 104 2842.65 25 0 0.896507
105 105 2862.65 25 0 0.896507
106 106 2882.65 25 0 0.896507
107 107 2902.65 25 0 0.896507
108 108 2922.65 25 0 0.896507
109 109 2942.65 25 0 0.896507
110 110 2962.65 25 0 0.896507
111 111 2982.65 25 0 0.896507
112 112 3002.65 25 0 0.896507
113 113 3022.65 25 0 0.896507
114 114 3042.65 25 0 0.896507
115 115 3062.65 25 0 0.896507
116 116 3082.65 25 0 0.896507
117 117 3102.65 25 0 0.896507
118 118 3122.65 25 0 0.896507
119 119 3142.65 25 0 0.896507
120 120 3162.65 25 0 0.896507
121 121 3182.65 25 0 0.896507
122 122 3202.65 25 0 0.896507
123 123 3222.65 25 0 0.896507
124 124 3242.65 25 0 0.896507
125 125 3262.65 25 0 0.896507
126 126 3282.65 25 0 0.896507
127 127 3302.65 25 0 0.896507
128 128 3322.65 25 0 0.896507
129 129 3342.65 25 0 0.896507
130 130 3362.65 25 0 0.896507
131 131 3382.65 25 0 0.896507
132 132 3402.65 25 0 0.896507
133 133 3422.65 25 0 0.896507
134 134 3442.65 25 0 0.896507
135 135 3462.65 25 0 0.896507
136 136 3482.65 25 0 0.896507
137 137 3502.65 25 0 0.896507
138 138 3522.65 25 0 0.896507
139 139 3542.65 25 0 0.896507
140 140 3562.65 25 0 0.896507
141 141 3582.65 25 0 0.896507
142 142 3602.65 25 0 0.896507
143 143 3622.65 25 0 0.896507
144 144 3642.65 25 0 0.896507
145 145 3662.65 25 0 0.896507
146 146 3682.65 25 0 0.896507
147 147 3702.65 25 0 0.896507
148 148 3722.65 25 0 0.896507
149 149 3742.65 25 0 0.896507
150 150 3762.65 25 0 0.896507
151 151 3782.65 25 0 0.896507
152 152 3802.65 25 0 0.896507
153 153 3822.65 25 0 0.896507
154 154 3842.65 25 0 0.896507
155 155 3862.65 25 0 0.896507
156 156 3882.65 25 0 0.896507
157 157 3902.65 25 0 0.896507
158 158 3922.65 25 0 0.896507
159 159 3942.65 25 0 0.896507
160 160 3962.65 25 0 0.896507
161 161 3982.65 25 0 0.896507
162 162 4002.65 25 0 0.896507
163 163 4022.65 25 0 0.896507
164 164 4042.65 25 0 0.896507
165 165 4062.65 25 0 0.896507
166 166 4082.65 25 0 0.896507
167 167 4102.65 25 0 0.896507
168 168 4122.65 25 0 0.896507
169 169 4142.65 25 0 0.896507
170 170 4162.65 25 0 0.896507
171 171 4182.65 25 0 0.896507
172 172 4202.65 25 0 0.896507
173 173 4222.65 25 0 0.896507
174 174 4242.65 25 0 0.896507
175 175 4262.65 25 0 0.896507
176 176 4282.65 25 0 0.896507
177 177 4302.65 25 0 0.896507
178 178 4322.65 25 0 0.896507
179 179 4342.65 25 0 0.896507
180 180 4362.65 25 0 0.896507
181 181 4382.65 25 0 0.896507
182 182 4402.65 25 0 0.896507
183 183 4422.65 25 0 0.896507
184 184 4442.65 25 0 0.896507
185 185 4462.65 25 0 0.896507
186 186 4482.65 25 0 0.896507
187 187 4502.65 25 0 0.896507
188 188 4522.65 25 0 0.896507
189 189 4542.65 25 0 0.896507
190 190 4562.65 25 0 0.896507
191 191 4582.65 25 0 0.896507
192 192 4602.65 25 0 0.896507
193 193 4622.65 25 0 0.896507
194 194 4642.65 25 0 0.896507
195 195 4662.65 25 0 0.896507
196 196 4682.65 25 0 0.896507
197 197 4702.65 25 0 0.896507
198 198 4722.65 25 0 0.896507
199 199 4742.65 25 0 0.896507
200 200 4762.65 25 0 0.896507
201 201 4782.65 25 0 0.896507
202 202 4802.65 25 0 0.896507
203 203 4822.65 25 0 0.896507
204 204 4842.65 25 0 0.896507
205 205 4862.65 25 0 0.896507
206 206 4882.65 25 0 0.896507
207 207 4902.65 25 0 0.896507
208 208 4922.65 25 0 0.896507
209 209 4942.65 25 0 0.896507
210 210 4962.65 25 0 0.896507
211 211 4982.65 25 0 0.896507
212 212 5002.65 25 0 0.896507
213 213 5022.65 25 0 0.896507
214 214 5042.65 25 0 0.896507
215 215 5062.65 25 0 0.896507
216 216 5082.65 25 0 0.896507
217 217 5102.65 25 0 0.896507
218 218 5122.65 25 0 0.896507
219 219 5142.65 25 0 0.896507
220 220 5162.65 25 0 0.896507
221 221 5182.65 25 0 0.896507
222 222 5202.65 25 0 0.896507
223 223 5222.65 25 0 0.896507
224 224 5242.65 25 0 0.896507
225 225 5262.65 25 0 0.896507
226 226 5282.65 25 0 0.896507
227 227 5302.65 25 0 0.896507
228 228 5322.65 25 0 0.896507
229 229 5342.65 25 0 0.896507
230 230 5362.65 25 0 0.896507
231 231 5382.65 25 0 0.896507
232 232 5402.65 25 0 0.896507
233 233 5422.65 25 0 0.896507
234 234 5442.65 25 0 0.896507
235 235 5462.65 25 0 0.896507
236 236 5482.65 25 0 0.896507
237 237 5502.65 25 0 0.896507
238 238 5522.65 25 0 0.896507
239 239 5542.65 25 0 0.896507
240 240 5562.65 25 0 0.896507
241 241 5582.65 25 0 0.896507
242 242 5602.65 25 0 0.896507
243 243 5622.65 25 0 0.896507
244 244 5642.65 25 0 0.896507
245 245 5662.65 25 0 0.896507
246 246 5682.65 25 0 0.896507
247 247 5702.65 25 0 0.896507
248 248 5722.65 25 0 0.896507
249 249 5742.65 25 0 0.896507
250 250 5762.65 25 0 0.896507
251 251 5782.65 25 0 0.896507
252 252 5802.65 25 0 0.896507
253 253 5822.65 25 0 0.896507
254 254 5842.65 25 0 0.896507
255 255 5862.65 25 0 0.896507
256 256 5882.65 25 0 0.896507
257 257 5902.65 25 0 0.896507
258 258 5922.65 25 0 0.896507
259 259 5942.65 25 0 0.896507
260 260 5962.65 25 0 0.896507
261 261 5982.65 25 0 0.896507
262 262 6002.65 25 0 0.896507
263 263 6022.65 25 0 0.896507
264 264 6042.65 25 0 0.896507
265 265 6062.65 25 0 0.896507
266 266 6082.65 25 0 0.896507
267 267 6102.65 25 0 0.896507
268 268 6122.65 25 0 0.896507
269 269 6142.65 25 0 0.896507
270 270 6162.65 25 0 0.896507
271 271 6182.65 25 0 0.896507
272 272 6202.65 25 0 0.896507
273 273 6222.65 25 0 0.896507
274 274 6242.65 25 0 0.896507
275 275 6262.65 25 0 0.896507
276 276 6282.65 25 0 0.896507
277 277 6302.65 25 0 0.896507
278 278 6322.65 25 0 0.896507
279 279 6342.65 25 0 0.896507
280 280 6362.65 25 0 0.896507
281 281 6382.65 25 0 0.896507
282 282 6402.65 25 0 0.896507
283 283 6422.65 25 0 0.896507
284 284 6442.65 25 0 0.896507
285 285 6462.65 25 0 0.896507
286 286 6482.65 25 0 0.896507
287 287 6502.65 25 0 0.896507
288 288 6522.65 25 0 0.896507
289 289 6542.65 25 0 0.896507
290 290 6562.65 25 0 0.896507
291 291 6582.65 25 0 0.896507
292 292 6602.65 25 0 0.896507
293 293 6622.65 25 0 0.896507
294 294 6642.65 25 0 0.896507
295 295 6662.65 25 0 0.896507
296 296 6682.65 25 0 0.896507
297 297 6702.65 25 0 0.896507
298 298 6722.65 25 0 0.896507
299 299 6742.65 25 0 0.896507
300 300 6762.65 25 0 0.896507
301 301 6782.65 25 0 0.896507
302 302 6802.65 25 0 0.896507
303 303 6822.65 25 0 0.896507
304 304 6842.65 25 0 0.896507
305 305 6862.65 25 0 0.896507
306 306 6882.65 25 0 0.896507
307 307 6902.65 25 0 0.896507
308 308 6922.65 25 0 0.896507
309 309 6942.65 25 0 0.896507
310 310 6962.65 25 0 0.896507
311 311 6982.65 25 0 0.896507
312 312 7002.65 25 0 0.896507
313 313 7022.65 25 0 0.896507
314 314 7042.65 25 0 0.896507
315 315 7062.65 25 0 0.896507
316 316 7082.65 25 0 0.896507
317 317 7102.65 25 0 0.896507
318 318 7122.65 25 0 0.896507
319 319 7142.65 25 0 0.896507
320 320 7162.65 25 0 0.896507
321 321 7182.65 25 0 0.896507
322 322 7202.65 25 0 0.896507
323 323 7222.65 25 0 0.896507
324 324 7242.65 25 0 0.896507
325 325 7262.65 25 0 0.896507
326 326 7282.65 25 0 0.896507
327 327 7302.65 25 0 0.896507
328 328 7322.65 25 0 0.896507
329 329 7342.65 25 0 0.896507
330 330 7362.65 25 0 0.896507
331 331 7382.65 25 0 0.896507
332 332 7402.65 25 0 0.896507
333 333 7422.65 25 0 0.896507
334 334 7442.65 25 0 0.896507
335 335 7462.65 25 0 0.896507
336 336 7482.65 25 0 0.896507
337 337 7502.65 25 0 0.896507
338 338 7522.65 25 0 0.896507
339 339 7542.65 25 0 0.896507
340 340 7562.65 25 0 0.896507
341 341 7582.65 25 0 0.896507
342 342 7602.65 25 0 0.896507
343 343 7622.65 25 0 0.896507
344 344 7642.65 25 0 0.896507
345 345 7662.65 25 0 0.896507
346 346 7682.65 25 0 0.896507
347 347 7702.65 25 0 0.896507
348 348 7722.65 25 0 0.896507
349 349 7742.65 25 0 0.896507
350 350 7762.65 25 0 0.896507
351 351 7782.65 25 0 0.896507
352 352 7802.65 25 0 0.896507
353 353 7822.65 25 0 0.896507
354 354 7842.65 25 0 0.896507
355 355 7862.65 25 0 0.896507
356 356 7882.65 25 0 0.896507
357 357 7902.65 25 0 0.896507
358 358 7922.65 25 0 0.896507
359 359 7942.65 25 0 0.896507
360 360 7962.65 25 0 0.896507
361 361 7982.65 25 0 0.896507
362 362 8002.65 25 0 0.896507
363 363 8022.65 25 0 0.896507
364 364 8042.65 25 0 0.896507
365 365 8062.65 25 0 0.896507
366 366 8082.65 25 0 0.896507
367 367 8102.65 25 0 0.896507
368 368 8122.65 25 0 0.896507
369 369 8142.65 25 0 0.896507
370 370 8162.65 25 0 0.896507
371 371 8182.65 25 0 0.896507
372 372 8202.65 25 0 0.896507
373 373 8222.65 25 0 0.896507
374 374 8242.65 25 0 0.896507
375 375 8262.65 25 0 0.896507
376 376 8282.65 25 0 0.896507
377 377 8302.65 25 0 0.896507
378 378 8322.65 25 0 0.896507
379 379 8342.65 25 0 0.896507
380 380 8362.65 25 0 0.896507
381 381 8382.65 25 0 0.896507
382 382 8402.65 25 0 0.896507
383 383 8422.65 25 0 0.896507
384 384 8442.65 25 0 0.896507
385 385 8462.65 25 0 0.896507
386 386 8482.65 25 0 0.896507
387 387 8502.65 25 0 0.896507
388 388 8522.65 25 0 0.896507
389 389 8542.65 25 0 0.896507
390 390 8562.65 25 0 0.896507
391 391 8582.65 25 0 0.896507
392 392 8602.65 25 0 0.896507
393 393 8622.65 25 0 0.896507
394 394 8642.65 25 0 0.896507
395 395 8662.65 25 0 0.896507
396 396 8682.65 25 0 0.896507
397 397 8702.65 25 0 0.896507
398 398 8722.65 25 0 0.896507
399 399 8742.65 25 0 0.896507
400 400 8762.65 25 0 0.896507
401 401 8782
```

Dynamic Aperture(DA) calculation with opttog4bl.csh




- In this figure, the DA is defined as the percentage of initial particles that can survive passing through the beamline.
- Give estimated x and x' range, then divide them to 20 divisions(steps);
- In each pixel(step), a random distribution of 1000 particles is generated, assuming x' and y' uniformly distributed within $\pm x'$ range defined previously; also the momentum is uniformly distributed within the momentum spread range($\pm \Delta P$);
- The virtual detector counts particles survived, get a percentage.

Multi-particle tracking in G4BL

From downstream of the horn to the ring. Red blocks show Quadrupoles and blue blocks show dipoles. Cyan lines are particle trajectories.

Use a virtual detector to measure number of particles at the end;



Always use pipes (Element "tub" in G4BL) to kill particles hitting the beam pipes

Tracking Results from Simulated Initial Pion Distribution


- Turn decay ON \rightarrow 90% survived;
- Turn decay OFF \rightarrow 96% survived — Corresponds to the theoretical decay percentage;

10000 2D Gaussian distributed π^+ 's generated by MATLAB code; RMS emittance = $0.5 \text{ mm} \cdot \text{rad} \left(\frac{\text{Acceptance}}{4} \right)$; $\beta_x = \beta_y = 5.525 \text{ m}$, $\alpha = 0$


Magnets configuration(In G4BL the fringe field was turned off;)

Magnet Name	Length (mm)	Distance to horn (From End of Magnet, mm)	Strength (T/m)	Beam pipe radius (mm)	Estimated pole-tip field (T)
Q1	500	700	6.09	200	1.22
Q2	900	1800	-10.18	200	2.04
Q3	900	2900	15.37	200	3.07
Q4	500	3716	-14.77	200	2.95
Q6	500	7600	-12.06	200	2.41
B1	2400	6884	-	width=400	1.213
QI1	900	8700	10.27	200	2.05
B2	800	9715	-	width=400	2.00
QI4	900	12041	-9.70	200	-1.94
QI5	900	13141	9.67	200	1.93
Q7A	500	16074	-10	200	2
B1	2400	18724	-	width=400	1.213
Q9	250	19224	10	200	2

Tracking Results from Simulated Pion Distribution(Cont'd)






Initial beam: $\sigma_{RMS,x} = \sigma_{RMS,y} \sim 5cm$






Final beam

Tracking Results from Pion Distribution (Courtesy of Sergei Striganov) Generated by MARS



Beam at downstream of the horn





Final beam: Turn decay ON \rightarrow Transmitted: $0.089/0.116=76.6\%$;

Turn decay OFF \rightarrow Transmitted: $0.095/0.116=82\%$.

X distribution of the beams shown in the previous slide.

Note: The weight is already taken into account; Left: Distribution after downstream of the horn; Right: Distribution at the end of transport;



Matching into Alex Bogacz's asymmetric ring larger beta straight


Beta functions in decay straight section ~ 46 meters; straight section ~ 150 meters. Straight to arc ratio is 6. 42% of pions decay in the straight.

Beta in the other straight
 ~ 8 meters

Total length of 350 meters;
Superconducting dipoles and
quadrupoles are required in
the arc.

Injection-Ring common section, after which $D_x=0$, $\alpha_x=-7.486$, $\alpha_y=3.07$, $\beta_x=12.57$ m, $\beta_y=28.36$ m

G4Beamline visualization of the asymmetric ring




Matching into Alex's asymmetric ring larger beta straight(Cont'd)


$\beta_x \sim 11$ meters, $\beta_y \sim 14$ meters, respectively.

Common section with the ring starts here

Total length of 21 m; time of flight 70 ns; in pion's frame 2 ns; fraction decayed $1 - \exp(-2/26) \sim 7.4\%$



DA calculation



Tracking Results from Simulated Initial Pion Distribution




- Turn decay ON → 74% survived;
- Turn decay OFF → 80% survived — Some of the decaying particles died before decay;

Same Gaussian distributed beam as described above (10000 particles, 0.5 mm-rad RMS emittance)




Magnets configuration (In G4BL the fringe field was turned off;)

Magnet Name	Length (mm)	Distance to horn (From End of Magnet, mm)	Strength (T/m)	Beam pipe radius (mm)	Estimated pole-tip field (T)
Q1	500	704	1.8	200	0.36
Q2	500	1410	-8.16	200	1.63
Q3	500	2129	14.92	200	2.98
Q4	500	3043	-15	200	3
Q5	500	3830	9.38	200	1.88
B1	852	4886	-	width=400	3.913
Q6	900	5986	-6.189	200	1.24
QI2	500	7459	15	200	3
B2	1200	8659	-	width=400	2
QI4	900	10745	-12.61	200	2.52
QI5	900	13092	10.482	200	2.10
Q7	500	14790	-26.8837	200	5.377
Q9	500	16390	23.8548	200	4.771
B1	852	17367	-	width=400	3.913
Q7A	500	20920	-8.042	200	1.608

Tracking Results from Simulated Pion Distribution(Cont'd)






Initial beam






Final beam

Tracking Results from Pion Distribution Generated by MARS



Beam at downstream of the horn





Final beam: Turn decay ON → Transmitted: 0.0822/0.116=71%;

Turn decay OFF → Transmitted: 0.0886/0.116=76.5%.

X distribution of the beams shown in the previous slide.

Note: The weight is already taken into account; Left: Distribution after downstream of the horn; Right: Distribution at the end of transport;





Summary of transport line study

We were able to achieve LOI- proposed 0.072 pions per POT that can be injected to the ring, according to the simulations of transport lines corresponding to our current ring scenarios.

Ring Simulation using G4Beamline

- Use a particlefilter(blue) at the beginning namely the end of the ring to limit the number of turns;
- Use a virtualdetector at the end of the ring to trace particles for each turn;
- Use a beamlosstuple to record the loss of each particle;
- Converted by opttog4bl.csh from OptiM: automatically connected to be a ring; if dipole edge effects are considered, genericbends rather than sectordipoles are used to simulate the edge effects.

A degree larger than 360 may cause an overlap of the last element and the first one, which results in failure of particlefilter killing. (Can view the angle from OptiM-Orbit)



First trial of simulation of the ring


- Starting with my ring since the dipoles are pure sector dipoles;
- The initial C-S parameters: $\beta_x=30$ m, $\beta_y=20$ m, $\alpha_x = \alpha_y = 0$
- Choose RMS emittance = $\frac{\text{Acceptance}=2\text{mm}\cdot\text{rad}}{4}=0.5$ mm · rad, different momentum spread($P_0=3800$ MeV)
- Simulation time will be long since there are hundreds of elements in one turn. Thus only 50 muons were used to perform the first step study.
- 100 turns = 64556 meters \rightarrow 215.2 microseconds \rightarrow 5.98 μs in muons' view $\rightarrow e^{-(5.98e-6)/(2.2e-6)}=0.0659$ survived assuming no loss but only decaying;

(30 cm radius magnet aperture)

Transmission	1 turn	100 turns
$\frac{\Delta P}{P_0}=0$	41/50	41/50
$\frac{\Delta P}{P_0}=0.1$	34/50	25/50

(No chromaticity correction)
Tunes crossed resonance lines for larger momentum spread; would consider adding sextupoles soon.


Automating ring beamline conversion with dipoles having edge effects



- Sector dipoles \rightarrow rectangular dipoles
- Real length(a line) is shorter than the sector arc length in optics design;(Need to consider that in G4Beamline)
- Center of the rectangular dipole should be displaced by the amount shown(both horizontally and vertically);
- Rotation angle of the dipole is always half of the bending angle.

Tuning the dipoles

To make sure the reference particle circulates the ring in a single circle rather than forming an envelope, we need to tune the dipoles to center the reference trajectory. To do this both the dipole field and the centerRadius of its corresponding cornerarc can be adjusted, to minimize the transverse reference offset and angle.



Transmission for Alex's Ring beamline

Transmission slightly lower compared to the previous ring scheme (This ring requires even larger aperture in the decay straight, since $\sqrt{\beta\epsilon} \sim 31$ cm already at max beta positions) – there is still no sextupole chromaticity correction. Also need to be further inspected.

(30 cm radius magnet aperture)

Transmission	1 turn	100 turns
$\frac{\Delta P}{P_0}=0$	35/50	34/50
$\frac{\Delta P}{P_0}=0.1$	29/50	10/50



Conclusions

- Two transport lines for the current FODO ring schemes have been developed, they are able to achieve ~ 0.085 pions / POT including decay;
- A SHELL script has been written to automate the conversion from OptiM lattice to G4BL input format, and is being updated based on specific requirements;
- The ring simulation using G4BL has been started and several different scenarios will be further tested.