

NEXT-100 Mechanical Overview

Derek Shuman

Lawrence Berkeley National Laboratory

December 3, 2012

Mechanical

- Derek Shuman LBNL (lead, past)
- Sara Carcel, IFIC (lead, present)
- Alberto Martinez, IFIC


Civil


- Jose Luis Perez Aparicio, University Polytechnica de Valencia (lead)
- Jordi Torrent Collell, Escola Politecnica superior, University de Girona
- Roberto Palma, UPV


Electrical


- Jose F. Toledo Alarcon, IFIC (lead)
- Javier Rodriguez Samaniego, IFIC
- John Joseph, LBNL





















End view of ICS bars showing possible external source collimators




Main Cylindrical Vessel

EL mesh planes

Cathode

EL HV F.T.




Reflectors

Field Cage Rings

F.C. Insulator


Cu Shield Bars

Shielding, External, Pb





Parameter	qty	units
Maximum Operating Pressure (MOP)	15.0	bar (abs)
Maximum Allowable Working pressure (MAWP)	16.4	bar (abs)
Minimum Allowable Pressure (external)	1.5	bar (abs)
Material, stainless steel, alloy	316Ti	
Inner diameter	136	cm
Outer Diameter, Flanges	148	cm
Length, inside shielding	2.22	m
Vessel and head wall thickness	10	mm
Flange thickness, head to vessel (both)	4.1	cm
Bolt Diameter (Inconel 718), head to vessel flanges	16	mm
Number of Bolts, each head to vessel flange	132	
Mass, Vessel and both heads	1100	kg
Mass, Internal copper shielding	8500	kg
Total Weight	12000	kg


Double seal detail with leak sense port





Interface flange detail













Hamamatsu R11410-10

**Front view of
R11410MOD**

Typical quantum efficiencies, as measured, from [arisaka]


Spectral Response Characteristics

Tube Type	R11410-10	Max. Q.E.	34.9 %
Serial No.	ZK6346	Wavelength of max.	320 nm
Date	Aug.24, 2011		
Tested by	H.OISHI		
Note			



Spectral Response Characteristics


Tube Type	R11410-10	Max. Q.E.	34.8 %
Serial No.	KAD001	Wavelength of max.	320 nm
Date	Aug.24, 2011		
Tested by	H.OISHI		
Note			



Katsushi Arisaka


Window strength assurance


- Strength is a strong function of area and finish (as well as intrinsic strength)
- Weibull distribution: failure probability vs. stress-area function
- Sapphire and quartz have well characterized Weibull parameters (moduli and characteristic strength)
- Choose thickness, finish to give low failure probability (5% or less) at a TEST pressure
- Test pressure set to assure: if no failure under test then no failure under fatigue (cyclic or static)
- Pressure Test all windows




(Temperature Drop, Base to ambient @1750V, 3.5M Ω)

Section	deg. C
Potting Compound, 1mm (1W/(m*K))	2.38
Kapton MT insulation, .05mm	0.33
Cu braid, 259 kcmil x 7.5cm	1.34
Contact, into backplate	0.04
Contact, into enclosure	0.02
Enclosure to Clamp	0.17
Contact into Carrier Plate	0.02
Carrier plate to convolution	0.22
Convolution to Vessel flange	0.48
Vessel flange	1.32
Total Temp Drop	6.3










- Design by James White, Clement Sofka, TAMU
- 3cm polyethylene rotomolded and machined
- 130 cm drift length, 25 cm cathode buffer region grade-down
- "C-clamp" EL mesh connection avoids sparking or tracking
- EL meshes and frame based on proven designs up to 50 cm dia.
- EL mesh of fine wire ($30\mu\text{m}$) and pitch (0.5mm), 88% transparent
- Coarse, stiff wire mesh on cathode for simplicity (88% transparent)


Drift field strength	0.3 kV cm^{-1}
EL field strength (E/p)	$3.0 \text{ kV cm}^{-1} \text{ bar}^{-1}$
Optical gain	$2500 \text{ photons/e}^{-}$
Drift length	130 cm
EL gap	0.5 cm
Cathode voltage	$-61.5 \text{ kV @15 bar (a)}$
Gate grid voltage	$-22.5 \text{ kV @15 bar (a)}$
Anode grid voltage	0







Tefzel insulator, will be graded on OD (contacts FC buffer grade down rings)









- 111 Dice Boards (DBs) 80mm square pitch, 64 SiPMs/DB
- DB is 4 layer Cufion multilam PCB, 80 pinout
- Xe flows around edges of each DB and behind them (no flow allowed elsewhere)
- DB carrier plate doubles as ICS shield (allows connectors inside vessel)
- ZIF connector (0.5mm pitch) on FPC cable attaches to DB pigtail, behind Cu shield
- Cables (FPC) are stripline, 50Ω for reduced capacitance to ground
- Cables bundled into 3 sets, rest on shelves cantilevered from shield
- Feedthrough is all-polyimide (Cirlex) multilayer rigid-flex circuit (42 FPCs/FT)
- Feedthrough made with a machined flange for internal sealing
- Metal flange and PV head removable from outside without disturbing cables







LBNL Feedthrough Stripline FPC Design Proposal

