Servers' technical specification

- Processors
 - Cores, frequency and features
- Interconnects
 - Sockets, PCIe lanes, etc.
- Memory
 - Capacity, bandwidth and channels
- Storage
 - Type, capacity and bandwidth
- Network
 - Bandwidth and features (e.g.: RDMA)
- Chipset & mainboard
 - Features (e.g.: on-board accelerators)

	Minimum Requirements	Recommended Requirements
Drive type	HDD	SSD
CPU	4 cores (8 logical threads),	8 cores (16 logical threads),
	frequency - 3-3.5 GHz and more	frequency - 3.5 GHz or more
RAM	8 GB or more	32 GB or more
Free disk space	200 GB or more	500 GB or more
Network interface bandwidth	100 Mbps	1 Gbps
HDD for IIS and documents	64 Gb	128 Gb

A database use-case oriented server spec.

Approach diagram



Example - Readout Unit

1. List of components mapped to server spec. needs

	Component	Devices and interconnects	CPU	Memory	Persistent storage
	Data reception	NICs and PCIe lanes	sensitive	sensitive	
ſ	Latency Buffer	Memory and its channels	marginal	sensitive	marginal
	Data processing	CPU and cache lines	sensitive	sensitive	
	Supernova Burst Data Store	Persistent storage	marginal	sensitive	sensitive

- 2. Methods for quantifying the resources needs
- 3. Tools to be developed tied to a list of methods Green: Developed Red: Refinement needed
- Test plan for measurements tied to tools and methods OK or ongoing:

Components/ what needs to be tested	Device feature and interconnects	CPU utilization	Memory utilization	Storage utilization
Data reception	Can be calculated, Acceptance tests of 100Gb NICs	Test 1.: DPDK reception Test 2.: Copy vs. callback Test 3.: integrated system no missed/dropped packets	Can be calculated, cross-checked with PCM (~10GB/s per 100G)	
Latency Buffer	Can be calculated, Max bandwidth I/O	Test 1.: Prod/consumer/ request rate stress tests	Can be calculated, Test 1.: maximum throughput tests	Tests: filewriter and LB to drive via zero copy
Data Processing	Cache size and locality sensitive, AVX2 capable CPU	Tests: TPG algo., emulator tests, TPG rate scaling, Integrated system		
SNB capture	Can be calculated, High-speed NVMe	Can be calculated, cross-checked with standalone benchmarks	Can be calculated, cross-checked with standalone benchmarks	Can be calculated, cross-checked with standalone benchmark



Status matrix

Needs clarification Partially available Work is ongoing or done

Subsystem and their servers	List of components mapped to server specification needs	Methods for quantifying the resource needs	Tools to be developed tied to a list of methods	Test plan for measurements tied to a list of tools and method
DAQ Computing Infrastructure <u>Servers:</u> IPMI, Facility, DAQ SW				
CCM Servers: CCM, Monitoring				
Readout <u>Servers:</u> Readout				
Dataflow <u>Servers:</u> Storage, DFO				
Trigger <u>Servers:</u> Trigger MLT				