

DUNE ND MEETINGS

DUNE ND MEETINGS

- General forum for discussing (Phase I) DUNE ND
- Topics include:
 - Discussion that spans across the detector consortia, including infrastructure
 - Physics studies and software/computing developments that impact ND design
 - Including studies for DUNE ND preliminary technical design report
 - Major developments from ND consortia
 - Should be presented and discussed within the consortium first
 - Periodic updates/status from ND consortia and subsystems
 - Phase II discussions remain with the Phase II organization
- Initial cadence of ~1/month

PHASE I ND REQUIREMENTS


- The DUNE ND Requirements task force has concluded and produced its initial report
 - Many thanks to the committee for this important work!
 - The draft report has been presented to the LBNC in the June meeting
 - They will provide feedback in the coming weeks
 - We would like to finalize the report shortly there after
 - Please have a look at the report (docdb 30591)
 - Thanks to those who have provided feedback already
 - Further feedback welcome until 12 July
- Chair: Mike Kordosky**
- **Physics Working Groups**
 - Long Baseline: L. Pickering
 - Cross Sections: L. Muntenuau
 - Exotics: J. Justo-Albo
 - Computing/Software: M. Muether
 - **ND consortia:**
 - ND-LAr: P. Ochoa Ricoux
 - TMS: D. Naples
 - SAND: M. Tenti

VERTICAL ALIGNMENT OF ND-LAr and TMS

From P. Tennessee (May ND TB Meeting)

Geometric centers of all detectors are currently on beam centerline

- Allowing a vertical offset would reduce cost by shrinking platforms under TMS and ND-LAr
- What accuracy is necessary for physics goals?




GOAL

- We would like to specify the vertical positions of ND-LAr, TMS
 - Specify = nominal \pm tolerance
 - Horizontal positions are largely irrelevant/moot since:
 - Along the beam direction, the detectors are highly constrained but we may eventually ask similar questions
 - Transverse to the beam, the detectors move with DUNE-PRISM . . . these are DUNE-PRISM accuracy requirements
- Ideally, we would perform a simulation to maximize acceptance, etc.
 - We don't have this . . . and even so, there would be ambiguity in what it means to "maximize acceptance"
- We have operated based on simple geometric considerations thus far
 - Several "reasonable" ways to specify a geometric consideration that lead to different nominal positions
 - See how much they quantitatively vary the implied vertical position
 - This can

STEPPING TOWARDS OUR SITUATION


- If the beam were truly horizontal, we would center both detectors vertically along the beam axis
- I think this is “obviously” what we would do
- We would still need a tolerance
- But the beam is tilted 5.79°
- If we could orient the detector in any way
 - “Just” tilt the detectors by the same amount
- But we keep the detectors horizontal
 - What does it mean to be “centered”?



CENTERING:

- “Centering” means different things for ND-LAr and TMS
- For ND-LAr, there is a “fiducial volume” in which we want to contain a neutrino interactions
 - Particles go roughly in the direction of the beam but some can go at wide angles and even backwards.
 - There should be a “buffer” around the interaction point so that particles can range out in all direction
 - Hence a “fiducial volume”: interactions within this volume have sufficient buffer of active LAr:
 - 50 cm from upstream face and top/bottom, 150 cm from back end (due to higher energy particles going forward.
- For TMS, there is no “fiducial volume” since we are looking at muons come from ND-LAr
 - They pass through the front face of the detector and go where they may
 - We want to maximize the possibility of intercepting that muon and its path through the TMS
 - Relevant alignment is with respect to ND-LAr
 - If ND-LAr is offset with respect to the beam, TMS should follow

ND-LAr



• Results

- a.) Raise detector +15 cm from nominal
- b.) “Nominal”
- c.) Lower detector -3 cm from nominal


• Three possible points to center:

- a.) start of ND-LAr fiducial volume
 - 50 cm downstream of upstream edge of active volume
- b.) middle of ND-LAr fiducial volume (+150 cm)
 - 200 cm downstream of upstream edge of active volume
 - “nominal”
- c.) middle of active volume (+200 cm)
 - 250 cm downstream of upstream edge of active volume

• Given upstream containment, centering further upstream of a.) doesn't make sense

• Given downstream containment of higher-energy “forward” particles, centering further downstream of c.) doesn't make sense

TMS



- Results

- α .) Raise detector +20 cm from nominal
- β .) Nominal
- γ .) Lower detector -15 cm from nominal


- Three possible points to center:

- α .) start of TMS (0 cm)
- β .) transition between fine/coarse region (+200 cm)
 - **Current nominal**
- γ .) middle of overall TMS (+350 cm)

- Doesn't make sense to center outside of the detector, so upstream of α doesn't make sense


- **Given entry of muons from upstream centering further downstream of γ doesn't make sense**

ND-LAR + TMS




- The beam axis does not directly pertain to TMS alignment
 - What matters is that it intercepts muons coming out of ND-LAR
 - However the beam axis also gives the axis on which the muons from ND-LAR will be centered
- Translate the range from the previous slide as TMS relative to ND-LAR (instead of beam axis)
- Redefine nominal b' (β') so that they are centered between $a(\alpha)$ and $c(\gamma)$ to center tolerance

MUON WINDOW




P. Tennesen

- A key feature of the ND-LAr cryostat is the downstream low-mass “window”
 - Skeleton steel structure to minimize energy loss for muons exiting ND-LAr and entering TMS while still providing mechanical support
 - Window vertical alignment should follow ND-LAr (like TMS)



CURRENT/PROPOSED CONFIGURATION



- Proposal:

- Due to structural margin and construction issues, reduce window height from 3.73(3.3) m \rightarrow 3.0(2.8) m
- Slight downward offset of window by 14 cm \rightarrow 116(164) cm above(below) beam axis

PROPOSALS:

- Position ND-LAr vertically so that the nominal beam-axis passes through center of the detector 100 cm from the upstream edge of the fiducial volume (150 cm from upstream edge of active volume) with ± 9 cm tolerance
- Position the Muon window such that a ray extending with 5.79 downward tilt from the vertical center of the ND-LAr active volume 150 cm from the upstream edge of its active volume passes 14 cm above the vertical center of the window, which has 2.8 (vertical) x 7 (horizontal) m² uniform area.
 - (Tolerance/area requirements to be defined)
- Position TMS vertically so that a ray extending with 5.79 degree downward tilt from the vertical center of the ND-LAr active volume 100 cm from the upstream edge of its active volume passes through the vertical center of TMS 175 cm from its upstream with +18/-18 cm tolerance