

Lattice Design and Beam Dynamics for a Future SCRF Linac Based Facility (Project-X)

Author1, Author2, Author3

Fermilab, Batavia, IL, 60510

Abstract abstract goes here

CONTENTS

1 Prologue	3
2 Introduction	3
2.1 Basic Concept	3
2.2 Staging	4
3 CW LINAC	6
3.1 Functional Requirements	7
3.2 Superconducting CW linac	8
3.3 LEBT	11
3.4 LEBT Design Principles	11
3.4.1 Emittance Growth due to Spherical Aberration	13
3.4.2 Emittance Growth due to Space Charge	14
3.5 The Project-X/PXIE LEBT	16
3.6 RFQ	23
3.6.1 Matched Parameters	24
3.7 MEBT	25
3.8 1 GeV Linac	26
3.8.1 HWR	26

3.8.2	SSR1	28
3.8.3	SSR2	29
3.8.4	LB650	29
3.8.5	HB650	30
3.9	1 GeV Turnaround	30
3.10	1-3 GeV Linac	30
3.11	3 GeV Linac	30
3.12	Pulsed Linac	30
3.13	Transport Lines	30
4	Beam Physics Studies	30
4.1	Acceptances	30
4.2	Effect of Beam Mismatch	31
4.3	Halo Formation and Losses in the Ideal Lattice	31
4.4	Beam Stripping	31
4.5	Electro-Magnetic (Lorentz) Stripping	31
4.5.1	Residual Gas	32
4.5.2	Black Body Radiation	32
4.5.3	Intra-beam stripping	33
5	HOM Excitation and Analysis	34
5.1	Longitudinal Modes	34
5.2	Transverse Modes	34
6	Failure Analysis	34
6.1	1 GeV	34
6.2	1-3 GeV	34
7	Start-to-end Simulations	35