


MICE Summary



Daniel M. Kaplan



May 31, 2014

Outline



Some MICE parallel session highlights

➤ with apologies to those whose slides I left out!

Conclusions

Parallel Session Presentations



- Presentations:
 - MICE Construction:
 - Virostek, Tartaglia, Witte, Prestemon
 - MICE Experiment:
 - Blackmore, Rajaram, Cremaldi, Drews/Winter, Leonova, Adey, Hanlet, Long

Spectrometer Solenoids (Virostek)



Empty high-bay at Wang NMR!




- Remaining tasks:
 - Upgrade SSU HTS lead connections
 & thermal intercepts
 - Vacuum tests / repairs as needed
 - Temperature sensor tests / repairs as needed >
 - Install downstream tracker & move SSD to MICE hall


to be done by LBL techs
to be done by LBL techs
@RAL early FY 15

Step IV Physics (Blackmore)



Summary





- A lot can be learned from Step IV
- Exactly <u>how much</u> depends on installation of Step V → <u>reacceleration</u> is the ultimate demonstration of ionisation cooling!

MAUS Software (Rajaram)



CONCLUSIONS

- MAUS can reconstruct data from every Step IV detector
- Capable of simulating the TOF, KL, and Tracker
 - EMR and Ckov in development
- The big gap is global track reconstruction
 - New manager, two students ramping up
- CAD-geometry implementation has progressed
 - Ongoing validation against full simulation
 - Usability and optimization issues to be evaluated
- Need to focus and make sure we have working simulation and reconstruction (beam + geometry + detectors + global) ready for Step IV

PID, Cherenkov (Cremaldi/Drews/Winter)





Stability Study: Positron Peaks




ins 02641-02691

- : 238 MeV/c
- :: 81.92 MeV/c

)3/2012

<u>Mean</u>	Uncertainty
105.1	2.1
152.0	3.0
116.6	2.4
96.4	2.2
126.9	2.6
156.3	2.7
124.8	2.5
127.9	2.5




30, 2014


MAP 2014 Spring Meeting | M. Drews, M. Winter

SS Mapping (Leonova)



SSU Field Measurements






Field *not* uniform to 1% over tracker volume? (Or did we mean ±1%?) Field disagrees with calculation based on "as-built" geometry How should currents be set for greater uniformity? Puzzles to work through...


Tracker HW & SW (Adey)





MAUS Tracker reconstruction working well!










State Machine Algorithm

For each subsystem & state, the algorithm:

Transitions:

- •manual
- •automatic

Note: states can be static or dynamic



Operations Planning (Long)



- Several complex tasks to orchestrate...
 - Ops Coordinator (Steve Boyd):
 - Needs to schedule work in concert with construction team;
 - Information gathering exercise the first step
 - Need to support this!
 - Commissioning windows:
 - -Will identify them as early as possible;
 - Do as much as possible WITHOUT BEAM
 - Discussion!



Two Concerns



1. Wedge test at risk

- Available funds for LiH wedge insufficient, new funds may be unavailable
- But wedge test very valuable
 - Not only demonstrates emittance exchange experimentally
 - Also potentially solves systematics problem in measuring dE/dx and straggling
- Need to simulate plastic wedge
 - If it works in simulation, should be cheap and quick to fabricate
- 2. Where & when test full-gradient cavities in realistic B field?
 - 16 MV/m requires 4 MW into a cavity, or 2 MW and LN₂ cooling
 - Do it once Step V beam program done?

Short Movie (Long)





MAP 2014 Spring Meeting (FNAL, 27-31 May 2014) | D. M. Kaplan, IIT

Conclusions



- MICE is progressing well towards early-2015 start of Step IV data-taking!
 - and Step V in 2018

But still much to do…

- ...and more hands needed!
- Discussions started with DOE on continuing support for MICE activity through Step V
- Hope to hear good news from NSF next month