

Aggregating local clouds with reusable tools

- Opportunities
- STAR experience & experiments
- Owning a pet local cloud



Jan Balewski
for STAR Collaboration



2014 OSG All Hands

April 7-11, 2014

SLAC, Menlo Park, CA

Why Cloud Computing?



- ✦ **significant computing resources ‘for rent’, ‘free?’**
- ✦ **virtualization benefits**
 - ✦ hardware-agnostic computation
 - ✦ easy recirculation of resources for different users (opportunistic resources)
 - ✦ natural preservation of software in VM ,‘as used’, for future re-use
- ✦ **challenges**
 - ✦ image config management : before of after launch ?
 - ✦ security, authorization, job scheduling
 - ✦ adopt to site-specific clouds ‘flavors’, aggregation (e.g. Phantom)
 - ✦ I/O data transfer, multi-site balancing to match variable computing resources
 - ✦ time : resources stability, startup , lease-time (on-availability)
 - ✦ cost: EC2, grants (Magellan), on-availability (STAR online 100% available during off-run periods)
 - ✦ education : ‘when will you restore my files on VM after last crash?’



STAR experiment at RHIC

~600 collaborators from
~50 institutions and ~12 countries

Reconstruction of particles emerging from collision
of two protons is a computational challenge



Brookhaven National Laboratory, Upton NY, USA



Former STAR encounters with VMs

date	Facility	tools	type of task	# of VMs	# jobs per VM	total CPU days	calendar days	total input (TB)	total output (TB)	remarks
2009, March	Amazon EC2	Nimbus Globus PBS batch	simu	100	1	500	5	0	0.3	works like normal globus GK grid site
2009, November	Amazon EC2	EC2	simu	10	1 or 2	1	1	0	0.01	use commercial interface
2010, February	GLOW Madison Uni Wisconsin	CondorVM	simu	430	1	130	0.6	0	0.1	call home model
2010, July	Clemson Uni, SC	Kestrel, QEMU-KVM	simu	1000	1	17,000	20	0	7	VM lifetime 24 h, no ssh to VM
2011, [Feb-May]	NERSC/ANL	Eucalyptus/ OpenStack	data reco	20...120	8	25,000+	120+	60	40	near real-time processing






Largest STAR simulations (ever) at Clemson

Matt Walker, MIT

- ✦ STAR MC simulations with partonic $p_T > 2$ GeV, PYTHIA event generator
- ✦ **Virtual Machine** prepared with STAR software stack and **deployed to over 1000 machines**
- ✦ Using cloud computing at **Clemson University in South Carolina** (Ranked #85 best supercomputer)



Available (red) and working (green) VMs track EXACTLY.


We clearly demonstrated that efficient use of truly **opportunistic** resources is possible and had a net gain/impact with no negatives for local jobs.




Multi-site STAR near real time data reco , June 2011

Magellan project resources
STAR experiment data/code


63 VMs
500 jobs



31 VMs
250 jobs



71 VMs
550 jobs




NERSC
cache
20 TB
gpfs




raw data: 3TB/day

reco events 2TB/day

BNL



STAR
experiment



RCF
HPSS

- coordination of data/storage and computation is not trivial.
- use the ANL resources efficiently, we had to transfer data from BOTH BNL->ANL and NERSC->ANL.



Irmo : the cloud of clouds

<http://press3.mcs.anl.gov/irmo/>

The Irmo project develops a vision for an infrastructure strategy that seeks to combine the different usage modalities present in DOE communities under one model that encourages collaborative sharing, supports community growth, accommodates emergent usage patterns such as on-demand computing, and lowers the entry barrier to the use of DOE facilities from desktop to exascale.

Highlights :

- develop best practices
- provide (identify exiting) tools to handle ease customization
- apply the same recipe even if the Cloud is made of several clouds (e.g. Phantom service)



VM formats - similar but different




3-part format (ami/aki/ari)

- 3 files must match
- bundling (i.e. chopping) is needed
- any kernel update requires re-bundling
- may exclude some (confidential) content
- (3x less) easy to copy
- VM disc size matches launch 'flavor'

vmdk format


- single image file (10-20 GB)
- whole VM image 'from outside'
- no bundling step
- easy to copy
- not elastic VM disc





VM content management

Dynamic contextualization




Michael Poat, BNL

- lightweight
- scripted (reusable)
- widely scalable to 1000's VMs
- policy syntax non-trivial
- tested even on submarines (limited internet access)

CFE is complementary to user-data injection at launch

Automatic code versioning



Dilemmas:


- 1 universal CFE policy & long VM boot time (which may fail), or
- archive each VM version (build once, use many times) & book-keep 100s GB of VM images
- IaaS may need site-specific VM changes → book-keep & archive 100s of VM images

We are exploring & learning



3.5% CPU losses due to virtualization

Reference : rcas6001 @ RCF/BNL
24 core, 48 GB RAM



```
bigArray= (double*)malloc(sizeB); // size=300MB
```

WORK UNIT: math & memory ops, no I/O

```
for(int i=0;i<nOps;i++) { // 'work'=math & memory operations
    int j=random()%sizeN;
    double x=random()*1./RAND_MAX, y=random()*1./RAND_MAX;
    double z=sin(x)*pow(y,1.123);
    bigArray[j]=z;
    j=random()%sizeN;
    bigArray[j]=pow( bigArray[j],2.3);
}
```

Timing measured by


```
clock_t begin = clock(); // CPU time in usec
```

```
time_t beginWallT; time(& beginWallT); // 1 second accuracy
```

Hardware: 4 **Workers**: Dell I950,
dual quad CPU (8cores) + 16GB RAM + 140 GB disc


Test 1) run jobs on 8-core hardware, Ubuntu 12

Test 2) run jobs inside 8vCore VM, SL 6.4







Ganglia monitoring inside each VM



Access to DNS name of host blade

- 149.165.158.65
- 149.165.159.43
- 149.165.159.48
- guest21.eucalyptus.sierra.futuregrid.org
- guest3.eucalyptus.sierra.futuregrid.org
- reuse40.lns.mit.edu
- reuse44.lns.mit.edu
- reuse46.lns.mit.edu
- reuse49.lns.mit.edu
- reuse51.lns.mit.edu
- reuse53.lns.mit.edu
- reuse55.lns.mit.edu
- reuse65.lns.mit.edu
- reuse67.lns.mit.edu
- s64r.idp.sdsc.futuregrid.org
- s66r.idp.sdsc.futuregrid.org

detect inefficient use of blades



2013++

Multiple clouds & interfaces

<https://portal.futuregrid.org>

(selected information about selected participants)

Selected Details of the Clusters

Name	Alamo	Bravo	Delta	Foxtrot	Hotel	India	Sierra
Organization	Texas Advanced Computing Center	Indiana University	Indiana University	University of Florida	University of Chicago	Indiana University	San Diego Supercomputer Center
Number of CPUs	192	32	32	64	168	256	168
Number of nodes	96	16	16	32	84	128	84
Total RAM (GB)	1152	3072	3072	768	2016	3072	2688
Number of cores	768	128		256	672	1024	672

Our focus: [site]-openStack sub-clusters, fraction of CPUs, **unified VM format**, similar to openStack at STAR-online, MIT-reuse, Amazon-EC2 clusters



One Phantom to rule them all

<https://phantom.nimbusproject.org/>

Pierre Riteau, U. Chicago



Phantom

Profile

App

Cloud Credentials

Cloud	Status
hotel-kvm	Disabled
india-openstack	Enabled
ec2-eu	Disabled
alamo	Enabled
hotel	Enabled
mit-openstack	Enabled
sierra-openstack	Enabled
wispy	Disabled
alamo-openstack	Enabled
ec2	Disabled
sierra	Enabled
hotel-openstack	Enabled
foxtrot	Enabled

hotel solo Launch Configuration

Appliance:

Contextualization
Type:

User Data

User Data

```
#!/bin/sh
echo "*****JAN: injecting test START
*****"
whoami
pwd ; ls -l
```

Save

Delete

Available Clouds

Cloud	Status
hotel-openstack	Enabled
alamo	Disabled
hotel	Disabled

Hotel-openstack Options

Maximum VMs:

6

Instance Type:

m1.large

Public Image


ami-00000034



Goal: distributed STAR data processing

'Cloud of the clouds' demonstrator

- outreach to Fermi/Cloud for a common activity and project
- exercise Phantom within Irmo project
- include on-availability component



Motivation

- ♦ participate in STAR data challenge on the cloud
- ♦ learn how to admin a local cloud
- ♦ let students learn how to use cloud resources (for free)

Choice: OpenStack (recycled hardware & free software)

- ♦ blades : Ubuntu 12.04 STL
- ♦ virtualization: devstack.org , **single script deployment**
- ♦ load monitoring : ganglia 2x
- ♦ blades (Dell 1950, 2850, 1650):
 - ♦ 8-core, kvm, small disc, 64-bit → **workers**
 - ♦ 4-core, qemu, large disc → **controller**, NFS storage
 - ♦ 32-bit blades → ganglia reporting, NFS storage
- ♦ blades connected at 1 GBit/sec : Catalyst 4000 switch
- ♦ flat network for VMs
- ♦ public class-C network: blades IP<100, VMs on demand


Controllers & utilities



24 8-core workers

iperf network bandwidth test

- a) MIT blade => FG: 707 Mbits/sec
- b) MIT blade => LBL: 267 Mbits/sec
- c) MIT VM => FG: 680 Mbits/sec
- d) MIT VM => LBL: 233 Mbits/sec



Paul Acosta, MIT

Simulations code

- ✦ SL6.5, Geant3, CERN ROOT
- ✦ GlueX software (C++)
- ✦ job profile: CPU intensive, large intermediate file, small output, ~no input



Strategy

- ✦ collaboration wide simu : JLAB, local computing centers, OSG
- ✦ each site assigned different range of random seeds (input)
- ✦ common output collection host
- ✦ simultaneous start of simulation
- ✦ produce as much as you can

Target MIT/FG contribution of 5 %



Measure Gluonic Excitations



Job authorization, scheduling, monitoring

#1 store ssh key for copying output

```
cat > id_rsa_tier2 <<EOF
-----BEGIN RSA PRIVATE KEY-----
MIIEowIBAAKCAQEAsqiRIBX2xOUnLnqyk0vRuA0jGAiie
yAiOwl7xb8b8YPa8/HIAtFmOYNXSxjYct9y8TSTu+PEX6
....
```

#2 redirect ganglia monitoring

```
sed -i "s/8663/${GANGLIAPORT}/g" /etc/ganglia/gmond.conf
service gmond restart
....
```

#3 install new GlueX binaries

```
wget http://reuse38.lns.mit.edu/glueX-dc-2/sim-recon-dc-2.7.tgz
tar -xzf sim-recon-dc-2.7.tgz
...
```

#4 copy in GlueX configuration files

```
wget http://reuse38.lns.mit.edu/glueX-dc-2/conditions/getSeed.sh
chmod a+x getSeed.sh
...
```

#5 write input script controlling pythia simulations

```
cat >> run.frr <<EOF
RUNNO    ${RUNNO}      run number of generated events
CRNDMSEQ \${SEED}      random number sequence
....
```

#6 runs the simulation <= THE JOB

```
hdgeant run.frr
....
```

#7 copy the output from VM to other location Tier2/Bates

```
scp -i id_rsa_tier2 -r dana_rest_0${RUNNO}_\${SEED}.hddm ....
```

Basic idea: user passes an individualized script to VM at launch, (is executed as root)

```
euca-run-instances -n 1 -t m1.small ami-000000009 \
-f helloWorld.sh
```

```
# cat helloWorld.sh
```

```
#!/bin/sh
```

```
echo "*****JAN: injecting test *****"
```

```
pwd ; whoami;
```

```
MYIP=`/sbin/ifconfig eth0 |grep Mask |cut -f2 -d: |cut -f1 -d\`
```

```
echo " Hello World from VM with local IP=$MYIP "
```

```
echo "*****JAN: test END *****"
```

Instance Console Log


```
Cloud-init v. 0.7.4 running 'modules:final' at Tue,
*****JAN: injecting test? *****
/
root
Hello World from VM with? local IP=10.50.0.23
*****JAN:? test END? *****
```

loop N
times

Justin Stevens, MIT

tally of resources allocated on various IaaS using Phantom


Site	Location	Openstack flavor	# Cores
<u>mit-stackb</u>	MIT	grizzly	136
hotel	University of Chicago	havana	100
india	Indiana University	havana	60
sierra	UC - San Diego	grizzly	56
<u>alamo</u>	University of Texas - Austin	<u>folsom</u>	0
total			352



Licensed software on VMs




VM/cloud help students/postdocs in general research





Visual Information Solutions






IDL. Discover What's In Your Data.

IDL is the trusted scientific programming language used across disciplines to extract meaningful visualizations from complex numerical data. With IDL you can interpret your data, expedite discoveries, and deliver powerful applications to market. Additionally, IDL is a truly cross-platform solution, providing support for today's most popular operating systems, including Microsoft Windows®, Mac OS X, Linux, and Solaris.

VMs on high core count blades
volatile MAC address

base VM image:

- SL6.5 (6 GB)
- Matlab (12 GB)
- IDL (2 GB)
- created ~10 users accounts
- assigned public IP after launch



Physical blade, fixed IP
hardware MAC adr.

FlexNet License Manager


- 3 Matlab licenses
- 3 IDL licenses

Summary

- demonstrated use of opportunistic resources, 'on-availability' is at reach
- building 'cloud of clouds' (Irmo) is complex task, many challenges
 - multi-site integration (e.g. Phantom) and site-to-site similarity (e.g. OpenStack)
 - VM content management : static VM master copy, in-fly CFEngine policy, user-data injection
 - security models: ssh-key, license server, Grid/GSI ?
 - job scheduling: condor, user-data injection, CFEngine policy
- virtualization provides time-capsules for task specific code & OS
- small local clouds based on surplus hardware allows for experimentation
- multi-thousand cores virtual cloud farms needed for practical applications




Backup




continuous write to NFS disc: Bad idea


writing to local disc inside VM




'stretch' elastic VM disc at launch: good idea



desynchronize jobs inside VM : good idea



"Cold start" of 94 VMs w/ 750 slots






multi-site condor inside VMs

user=balewski
@reuse06




Submit Jobs

LNS/MIT
condor installed
native in SL 6.4



Report Status / Run User Jobs

india OpenStack
condor installed
in VM SL 6.4



domain:
149.165.158.*

*.lns.mit.edu

Example of fully loaded condor cluster w/ one controller,
consisting of CPU 20 slots (5 machines x 4 slots)

```
[root@reuse06 ~]# condor_status
```

Name	OpSys	Arch	State	Activity	LoadAv	Mem	ActvtyTime
------	-------	------	-------	----------	--------	-----	------------

Condor-Controller+worker_0 @ native SL6.4_MIT

slot1@reuse06.lns.mit	LINUX	X86_64	Claimed	Busy	0.000	8026	0+00:00:04
slot2@reuse06.lns.mit	LINUX	X86_64	Claimed	Busy	0.000	8026	0+00:00:05
slot3@reuse06.lns.mit	LINUX	X86_64	Claimed	Busy	0.140	8026	0+00:00:06
slot4@reuse06.lns.mit	LINUX	X86_64	Claimed	Busy	0.000	8026	0+00:00:07

Condor-worker_1 @ native SL6.4_MIT

slot1@reuse05.lns.mit	LINUX	X86_64	Claimed	Busy	0.000	8026	0+00:00:04
slot2@reuse05.lns.mit	LINUX	X86_64	Claimed	Busy	0.000	8026	0+00:00:04
slot3@reuse05.lns.mit	LINUX	X86_64	Claimed	Busy	0.000	8026	0+00:00:05
slot4@reuse05.lns.mit	LINUX	X86_64	Claimed	Busy	0.000	8026	0+00:00:06

Condor-worker_2 @ native SL6.4_MIT

slot1@reuse07.lns.mit	LINUX	X86_64	Claimed	Busy	0.000	8026	0+00:00:04
slot2@reuse07.lns.mit	LINUX	X86_64	Claimed	Busy	0.000	8026	0+00:00:05
slot3@reuse07.lns.mit	LINUX	X86_64	Claimed	Busy	0.000	8026	0+00:00:06
slot4@reuse07.lns.mit	LINUX	X86_64	Claimed	Busy	0.080	8026	0+00:00:07

Condor-worker_3 @ VM_india_openstack

slot1@149.165.158.49	LINUX	X86_64	Claimed	Busy	0.340	1999	0+00:00:04
slot2@149.165.158.49	LINUX	X86_64	Claimed	Busy	0.000	1999	0+00:00:05
slot3@149.165.158.49	LINUX	X86_64	Claimed	Busy	0.000	1999	0+00:00:06
slot4@149.165.158.49	LINUX	X86_64	Claimed	Busy	0.000	1999	0+00:00:07

Condor-worker_4 @ VM_india_openstack

slot1@149.165.158.55	LINUX	X86_64	Claimed	Busy	0.000	1999	0+00:00:04
slot2@149.165.158.55	LINUX	X86_64	Claimed	Busy	0.000	1999	0+00:00:05
slot3@149.165.158.55	LINUX	X86_64	Claimed	Busy	0.000	1999	0+00:00:06
slot4@149.165.158.55	LINUX	X86_64	Claimed	Busy	0.000	1999	0+00:00:07

	Total	Owner	Claimed	Unclaimed	Matched	Preempting	Backfill
--	-------	-------	---------	-----------	---------	------------	----------

X86_64/LINUX	20	0	20	0	0	0	0
--------------	----	---	----	---	---	---	---

Total	20	0	20	0	0	0	0
-------	----	---	----	---	---	---	---

Original idea, discussion of implementation

<https://sites.google.com/site/patrickbwarren/ec2-condor-cluster>

<http://www.isi.edu/%7Egideon/condor-ec2/>