


# CPU Benchmarking at *GridKa*

– Update Nov. 2007 –



**Manfred Alef**

Grid Computing Centre Karlsruhe (GridKa)

Forschungszentrum Karlsruhe  
Institut für Wissenschaftliches Rechnen  
Hermann-von-Helmholtz-Platz 1  
D-76344 Eggenstein-Leopoldshafen

<http://www.fzk.de>, <http://www.gridka.de>

*firstname.lastname@iwr.fzk.de*

FALL HEPiX  
2007

## CPU Benchmark Talks to Last HEPiX Conferences:

- Measurements in GridKa environment:
  - Operating system: Scientific Linux 3 or 4, i386
  - Compiler: gcc-3.4.x
- Benchmark used: SPEC CPU2000
- Metric: SPECint\_base2000
  - Run 1 benchmark per core in parallel –  
the total box performance is the sum of all results.

SPEC®, SPECint®, and SPECfp®99 are registered trademarks  
of the Standard Performance Evaluation Corporation (SPEC).

## New: Switched to SPEC CPU2006:

- The SPEC CPU2000 benchmark suite has been retired by SPEC in February 2007 and replaced by the new CPU2006 suite.

Results submissions to SPEC's web page (<http://www.spec.org>) are no longer being accepted.

(However, the SPEC CPU2000 benchmark is still used within the HEP community, e.g. for accounting purposes in the WLCG project.)

## New: Switched to "Rate" Metric:

- The SPEC CPU benchmarks provide 2 metrics:
  - ◆ Speed: Is used for comparing the ability of a computer to complete single tasks.
  - ◆ Rate: Measures the throughput of a machine carrying out a number of jobs.  
Multiple copies of the benchmarks are run simultaneously. (Typically, the # of copies is the same as the # of CPU cores on the machine.)

## New: Switched to "Rate" Metric:

- In SPEC CPU2006, there is no longer a difference between the measurements of a speed run and a "1 copy" rate run.

(In contrast to that, these numbers differ by a factor of 0.011...0.012 when the SPEC CPU2000 suite is used.)

## New: Integer + Floating Point Measurements:

- The SPEC CPU benchmarks provide 2 sets of software packages:
  - ◆ Integer benchmarks (e.g., CINT2000 or CINT2006), C, C++.
  - ◆ Floating point benchmarks (e.g., CFP2006), C, C++, FORTRAN 77, Fortran 90, Fortran 95.  
*Compiler issues ...*

More info: <http://www.spec.org/cpu2006/CINT2006/>  
<http://www.spec.org/cpu2006/CFP2006/>

## New: Using GCC 4.x for SPEC CPU2006 Measurements:

### → Fortran compiler:

- ◆ GCC 3.x (g77) doesn't compile source code written in Fortran 90 or Fortran 95.
- ◆ GCC 4.x (gfortran) does it!
  
- ◆ *Scientific Linux 4 comes with GCC 3.4.x (default) + GCC 4.1.x (gcc4, g++4, gfortran).*

## Differences between SPEC CPU2000 and CPU2006:

### → Memory footprint:

- ◆ Some of the packages coming with CPU2000 fit into the cache. They by-pass the memory bottleneck.
- ◆ The new benchmarks will use much more RAM and can't escape from a memory bottleneck.

*At least 1 GB (i386) or 2 GB RAM (x86\_64) per benchmark copy are required.*

## Differences between SPEC CPU2000 and CPU2006:

### → **Benchmark workload:**

The new benchmarks will use a much bigger workload.

- ◆ The run time of the CINT2000 integer benchmark suite was about 2 hours on recent cluster hardware.
- ◆ A CINT2006 run takes at least one day.

(Reportable runs, "size=ref".)

## Benchmark Results:

→ **Benchmark environment – worker nodes at GridKa:**


- ◆ Intel Pentium-3 1.26 GHz 2001 – 2002
- Intel Xeon 3.06 GHz 2004
- AMD Opteron 270 (2.00 GHz dual-core) 2006
- Intel Xeon 5160 (3.00 GHz dual-core) 2007
- Intel Xeon E5345 (2.33 GHz quad-core) 2007 – 2008

Dual CPU, 0.5-2 GB RAM per core, 1 hard disk (E5345: 2 disks)

## Benchmark Results:


- **General remarks about optimizing flags:**
  - ◆ “HIGH optimization” (measure “best” performance):  
-O3 -funroll-loops [-march]
  - ◆ “LOW optimization” (flags used by LHC experiments):  
-O2 -pthread -fPIC

## Average CPU Core Performance (SPECint\_base2000, i386)




SL 3/4 i386, gcc-3.4.x ■ HIGH optimization, 1 benchmark copy per core, average performance per core

## Average CPU Core Performance (SPECint\_rate\_base2006, i386)




SL 3/4 i386, gcc-4.1.x    █ HIGH optimization, 1 benchmark copy per core, average performance per core


## Average CPU Core Performance (SPECint\_rate\_base2006, i386 / x86\_64)




## Average CPU Core Performance (SPECint / fp\_rate\_base2006, i386)




## Average CPU Core Performance (SPECint / fp\_rate\_base2006, x86\_64)



All results by AMD:  
OS=SLES 10 x86\_64




## Average CPU Core Performance (SPECint / fp\_rate\_base2006, x86\_64)



## Benchmark Results – “LOW” Tuning:


- Some HEP experiments are using another set of compiler flags:  
-O2 -pthread -fPIC
- How do the results differ?

## Average CPU Core Performance (SPECint\_base2000, i386)




SL 3/4 i386, gcc-3.4.x    **HIGH**    **LOW** opt., 1 benchmark copy per core, average performance per core

## Average CPU Core Performance (SPECint\_rate\_base2006, i386)




SL 3/4 i386, gcc-4.1.x    **HIGH**    **LOW** opt., 1 benchmark copy per core, average performance per core

## Average CPU Core Performance (SPECint\_rate\_base2006, i386 / x86\_64)



## Average CPU Core Performance (SPECint / fp\_rate\_base2006, i386)



## Conclusions (1):

- SPEC CPU2000 measurements on recent hardware are somewhat too optimistic.
- SPEC CPU2000 has been retired and replaced by its successor CPU2006.

## Conclusions (2):

- SPEC CPU2006 results:
  - ◆ Larger memory footprint → cache issues removed.
  - ◆ No difference in ramp-up 2001–2007 between high and low optimized measurements!
  - ◆ Performance 32bit → 64bit OS:  
Opteron +10% :-), Xeon -10% :-(.
  - ◆ Floating point measurements:  
Opteron ≈ 10% faster than Xeon  
(compared with integer performance).

## Comments, Questions?